

ADVANTEK® 10xW SERIES (WIDE RIM, WEATHERIZED)



RATING

For no rating, leave blank

H = Hurricane Rated

F = Fire Rated (Less/No Dogging Only)

FH = Hurricane and Fire Rated

OUTSIDE TRIM / DEVICE FINISH

605 = Polished brass (PVD)

606 = Brushed brass (PVD)

611 = Polished bronze (PVD)

612 = Brushed bronze (PVD)

613 = Oil rubbed bronze

625 = Polished chrome

626 = Brushed chrome (std. on lever trims)

628 = Aluminum, powder coated (device only)

629 = Polished stainless steel

630 = Brushed stainless steel (std. on pull trims & device)

693 = Black, powder coated

695 = Dark bronze, powder coated

DOGGING FUNCTION

LD = Less/No dogging

HD = Hex key dogging

CD = Cylinder key dogging

PRE-INSTALLED CYLINDERS

If cylinders provided by others, leave blank

MC65 = Mortise Cylinder(s) 6pin/Keyed 5

IC7 = Mortise Cylinder(s) SFIC housing

IK7 = Mortise Cylinder(s) InstaKey housing

RC65 = Rim Cylinder(s) 6pin/Keyed 5

IC7R = Rim Cylinder(s) SFIC housing

IK7R = Rim Cylinder(s) InstaKey housing

POWER TRANSFERS

For no power transfers, leave blank

FC3W = 3' Weatherized Flex Conduit

FC10W = 10' Weatherized Flex Conduit

FASTENERS

For standard machine, wood & self-drilling screws, leave blank

SN1 = Sex Nuts/ Throughbolts (Hurricane rated hardware includes sex nuts for latch bolt)

KNURLING

For no knurling, leave blank

KN = Knurled (lever trim only)

SERIES TYPE

10xW = Weatherized Rim device, wide stile (non-electrified)

STRIKES

98 = Semi-Mortise

99 = Surface*

94 = Double-Door (least secure)

ENDCAP

EC1 = Ramped endcap*

EC2 = Flush endcap

DOOR WIDTH

24" wide door

30" wide door

36" wide door (3')*

48" wide door (4')

SILENCER

For standard pushpad, leave blank

SLR = Silent Latch & Pushpad

OUTSIDE TRIM FUNCTION

For no outside trim, leave blank

01C = Exit only, blank plate

01W = Exit only, wide blank plate - long

02C = Dummy pull trim

02Z = Inactive Vandal pull handle (handed)

03C = Key retracts latch; pull trim

03Z = Key retracts latch; Vandal pull handle (handed)

03W = Key retracts latch; wide plate - long

03WS = Key retracts latch; plate - short

01D = Blank escutcheon

02D = Dummy lever trim

08D = Active lever, key locks / unlocks lever; Wide

lever handle (handed) (J, Q, S, T, U or

FSB1076 lever**) (classroom)

09D = Lever trim active by key, locked when key

removed; Wide lever handle (handed) (J, Q, S,

T, U or FSB1076 lever**) (storeroom)

14D = Active lever, no key cylinder; Wide lever

handle (handed) (J, Q, S, T, U or FSB1076

lever**) (passage)

CBK = Cylinder bracket kit, 03 only, plate & pull handle

by others required

EU = Electric Unlock Trim (24VDC & Fail Secure

[FSE] Std.) - Specify handing (not field

reversible). For 12VDC specify 12VDC. For Fail

Safe specify FSA

DOOR HANDING

RHR = Right hand reverse*

LHR = Left hand reverse

KEYSTOP

For no keystone, leave blank

KS = Keystop (Available with EB W functions)

ELECTRIFIED FUNCTION

For no electrified function, leave blank

Weatherized Alarms

Select Arming Time and Auto Rearm

EB W = Electric Battery Operated Exit Alarm Weatherized

EB EX W = Electric Battery Operated Exit Alarm Weatherized with

Request To Exit (Signal) Switch

EB EXV W = Electric Battery Operated Exit Alarm Weatherized with

Request To Exit (3Amp Current) Switch

Latch Retraction

ER EX W = Electric Latch Retraction Weatherized

with Request To Exit Switch

(silencer standard)

Power Supply / Controller for Latch

Retraction Only (ER EX W)

Order/Sold Separately

Single = 81-800

Pair = 82-800

2 Independent Singles = 83-800

Weatherized Others

ER EX W = Electric Latch Retraction

Weatherized with Request To Exit Switch (silencer standard)

EX W = Request To Exit (Signal) Switch Weatherized

EXV W = Request To Exit (3Amp Current) Switch Weatherized

WDE = Weatherized Delayed


Egress (see EasyKits)

Fire-rated trims must be fail safe (FSA)

**Other FSB levers available: 1016, 1035, 1058, 1075, 1093, 1119, 1147. FSB levers available in 630 finish only. See catalog pages for more information.

NOTE: * = default/standard

Also see online version at detex.com/hto



June 13, 2022