

Grade 2, medium-duty deadbolts

D200 Series

Overview

Deadbolt locks provide an extra measure of protection against break-in when used as a supplement to an existing lockset. In applications ranging from military and government projects to multi-family housing, retail and restaurants, Falcon® deadbolts deliver superior performance and the flexibility of multiple keying systems. Our full line of Grade 1 and 2 auxiliary locks feature interchangeable cores that are compatible with SFIC products from other manufacturers. Plus they're backed by Allegion, the best name in the business.



Finishes



605 Bright Brass



606 Satin Brass



613 Oil Rubbed Bronze



625 Bright Chrome



626 Satin Chrome



FALCON®

Grade 2, medium-duty deadbolts D200 Series

Cylinders

Conventional cylinder

L	Less 6-pin conventional cylinder
Р	6-pin conventional cylinder (pinned to 5)
P6	6-pin conventional cylinder (pinned to 6)
P7	7-pin conventional cylinder (pinned to 7)
CP6	6-pin conventional cylinder, Schlage C

Small format interchangeable core (SFIC)

В	Less SFIC
BB	7-pin SFIC, Best style
BDC	SFIC disposable construction core
G ¹	SFIC, Falcon style ¹
н	SFIC refundable construction core

1 6-pin standard, specify G7 if 7-pin is desired.

Availability of conventional cylinders in competitive keyways (6-pin)

The D Series lockset can be ordered with a conventional cylinder in a number of competitive open keyways. For a complete list of options see the Falcon catalog or price book.

Compatibility with competitors' SFIC cylinders

Falcon locksets also accept the following cores:

- Schlage
- Arrow (including Flex Core)
- Best (including PKS and Peaks)
- InstaKey
- Kaba Peaks
- Keymark
- KSP

When specifying "B" for less SFIC cylinder, please note that these manufacturer's cylinders all fit the Falcon lever and spring cage configuration. The appropriate Falcon tailpiece will be provided with the lockset.



FALCON

Grade 2, medium-duty deadbolts D200 Series

Functions



D211 Falcon ANSI E0172 **Classroom function**

- Deadbolt thrown or retracted by key from outside.
- Inside turn will only retract bolt. .
- Bolt automatically deadlocks when fully thrown.



Falcon D221 ANSI E016 Single cylinder

- Deadbolt thrown or retracted by key only.
- Blank plate inside.
- Bolt automatically deadlocks when fully • thrown.



No outside trim.

thrown.

Bolt automatically deadlocks when fully

.

D231

E0142

- Deadbolt thrown or retracted by key from either side.
- Bolt automatically deadlocks when fully . thrown.



Bolt automatically deadlocks when fully thrown.

Bolt automatically deadlocks when fully thrown.

Application for shelters.



Thumbturn

Key

FALCON_®

Functions



FalconD261MANSIE01112Thumbturn with rose

- Deadbolt thrown or retracted by turn unit only.
- No outside blank rose.
- Bolt automatically deadlocks when fully thrown.



Falcon D271 ANSI -Thumbturn (Inside with

occupancy indicator)

- Deadbolt thrown or retracted by turn unit only.
- Occupancy indicator on outside (reads either in use or vacant with color coding).
- Bolt automatically deadlocks when fully thrown.
- Emergency key supplied.





Specifications

Material	Solid zinc bolt with hardened steel anti-saw pin
Door thickness	1 ³ / ₈ " to 2 ¹ / ₄ " standard conventional cylinder
	1 ⁵ / ₈ " to 2" SFIC cylinder
Trim	
Handing	Non-handed
Deadbolt	
Backset	2 ³ / ₈ "- 2 ³ / ₄ " adjustable deadbolt
Faceplate	Standard: 1 ¹ / ₈ " x 2 ¹ / ₄ "
	Optional: 1" x 2 1/4"
Bolt	Deadbolt locks are furnished with deadbolts which have a full 1" projection.
	Housed within the deadbolt is a free-turning, $1/4$ " thick, hardened steel, saw-
	resistant roller. D200 bolt is cast zinc.
Strike	2 ³/4" x 1 ¹/8" lipless standard. ANSI 4 7/8" x 1 ¹/4" lipless, 2 ¹/4" full lip strikes, a
	2 ³ /4" x1 ¹ /8" T-strike or a security strike are available.
Keying	
Cylinder	Conventional cylinder, drilled with 6-pin chambers, pinned in 5 comes standard.
formats	Pinning in 6 chambers available (at no cost) when specified. Optional 7-pin
	conventional and 6- or 7-pin Small Format Interchangeable Core (SFIC)
	cylinders. Cylinder housings and plugs machined from solid brass. Springs are
	phosphor bronze. Two nickel silver keys furnished standard.
Keyways	"G" keyway standard on conventional cylinders; "A" keyway standard on SFIC
	cylinders. Additional options: Falcon, Schlage and many Best and Arrow keyways
Screws	Furnished with wood/machine screws for use on wood or metal doors or frames
	Furnished with wood/machine screws for use on wood or metal doors or frames
Warranty	
	Limited warranty, 10 years for date of manufacturer, see price book for details
Certifications	
ANSI/BHMA	A156.5, 2001, Grade 2
UL/cUL	Available UL Listed for 3-Hour fire door
Federal	BAA Listed
Other	ADA compliant thumbturn
	Abs complane combine