


(F)25-V Surface Vertical Device

Surface Vertical Rod Panic and Fire Exit Devices, Wood Door, LHR Shown, RHR Opposite



BACKSET			
Installation	3 1/2\" Min. Stile	4\" Min. Stile	4 1/2\" to Flush Door
Two Vertical Rod Devices	1 3/4\"	—	2 3/4\"
Vertical Rod x Mortise Device	—	2 3/4\"	2 3/4\"
Vertical Rod x Rim Device (1609 strike)	—	2 3/4\"	2 3/4\"

- Drill 1/8\" (3 mm) diameter x 1\" (25 mm) deep, or refer to Template W-4014 for sexbolt preparation (8 holes).
- **Fire rated devices require sexbolts.**

- For exit only device or device with non-thrumbing trim, drill 1/8\" (3 mm) diameter x 1\" (25 mm) deep, or refer to Template W-4014 for sexbolt preparation (4 holes).
- For device with thrumbing trim, refer to trim template.
- **Fire rated devices require sexbolts.**

- For exit only device, drill 2\" diameter, half of door thickness depth. For trim applications, drill through.

- For applications over 8 feet, install two rod guides equally spaced on top rod.
- For Less Bottom Rod (LBR) application (20 minute rating), refer to template W-5494 for auxiliary fire latch preparation, and omit bottom rod preparation.
- For sexbolt preparation, refer to Template W-4014.
- For outside trim, see trim template for door preparation.
- For 25-V device on ANSI A115.2 doors, see template W-1261.

TEMPLATE
W-1215-b