

## **Commercial In-Floor Safes**



In floor safes are designed to be buried in the floor and concealed by a dust cover under a rug or carpet. Installation should be done by a professional safe dealer.

## **Standard Features**

- UL listed, S&G Group II combination lock
- Hard plate between the lock and dial ring.
- Full length locking bar hinge side of door.
- Independent relocking device to deter forced entry.
- Door frame is reinforced on bolt side.

- Coil spring assist on all doors for ease of opening and closing.
- Dust cover included.
- "B" rate burglary construction.
- 5 active 3/4" bolts on Models 1307, 1311 and 3600.

## Square Tube Safe with Liftout Head

	Outside Dimensions			Inside Dimensions			Inside Cubic	Approx.	Door
Model	Н	W	D	Н	W	D	Inches	Wt. (lbs.)	Size
G500	8"	8"	11¼"	7%"	7%"	9"	523	42	7½"x7½"x1/2"
G700	8"	8"	15¼"	7%"	7%"	13"	755	51	7½"x7½"x1/2"

## Commercial In-Floor Safes

	Outside Dimensions			Inside Dimensions			Inside Cubic	Approx.	Door
Model	Н	W	D	Н	W	D	Inches	Wt. (lbs.)	Size
B1307*	14¾"	12¾"	12¼"	13¾"	12½″	8"	1375	100	12"x12"x1/2"
B1311*	14¾"	12¾"	17¼"	13¾"	12½"	13"	2234	117	12"x12"x1/2"
G3600*	23½"	12½"	17¼"	22¾"	12"	13½″	3686	150	12"x12"x1/2"

Standard color: Gray. All specifications are subject to change without notice. \*5 active locking bolts. Depth equals measurement into the ground. Width is left to right.