



Your Best Protection Against Fire and Theft

Visit us online at

www.gardall.com

MADE IN THE U.S.A.



Designed for complete protection of your valuables, a "B" rated burglary safe securely welded inside a 2-hour fire resistive safe.



Standard Features

- Class "B" Rated interior safe construction. Door of inner safe will interchange with other Gardall safes key lock or combination.
- Fire Resistive Exterior Safe – Insulated to withstand 1850°F for 2 hours.
- UL listed, S&G Group II combination lock
- Relocking Device – If back cover is knocked off of the lock, the independent relock device is activated, preventing bolt withdrawal.
- Boltwork Interior Door – Triple boltwork with independent relock device (except Models 1812 and 1818).
- Boltwork Exterior Door – Interlocking bolts extend into the safe walls, deadbolts on hinge side of door to deter forcible entry by removal of hinges.
- Hard plate on both interior and exterior door.
- Available with electronic push-button lock.



Safe/Chest Combo

Model	Outside Dimensions				Inside Dimensions			Inside Cubic Inches	Appx. Wt. (lbs.)	Shelves
	H	W	D		H	W	D			
Z1812/2	25"	17¼"	19¾"	MS	9¾"	11"	8"	858	365	NA
				SS	7¾"	12"	10¾"	1000		
Z1818/2	25"	17¼"	25¾"	MS	9¾"	11"	14"	1502	455	NA
				SS	8"	12"	16¾"	1608		
Z2218/2	29¼"	23¼"	25¾"	MS	12½"	17¼"	14"	3019	645	NA
				SS	9"	18"	16¾"	2714		
Z3018/2	37¼"	23¼"	25¾"	MS	12½"	17¼"	14"	3019	740	2
				SS	17½"	18"	16¾"	5162		
Z3620	43½"	25¾"	26¾"	MS	12½"	19½"	15¼"	3717	940	2
				SS	23¼"	20½"	18¾"	8937		
Z4220	49½"	25¾"	26¾"	MS	12½"	19½"	15¼"	3717	1010	3
				SS	29¼"	20½"	18¾"	11243		
Z4820	55½"	25¾"	26¾"	MS	12½"	19½"	15¼"	3717	1110	3
				SS	35¾"	20½"	18¾"	13595		

Standard colors: Gray or sandstone. Add 2" to outside depth for dial and handle.

Safe/Chest Combination - TL15 Money Safe/Two Hour Fire Safe



Model	Outside Dimensions				Inside Dimensions			Inside Cubic Inches	Approx. Wt. (lbs.)
	H	W	D		H	W	D		
SC1230	55¾"	25¾"	26¾"	Top	11¾"	12"	11"	1158	1695
				Bottom	30½"	20½"	20"	12505	

Weights measured w/pallet. Shelves SC1120 – 2, SC1130 – 3. All specifications are subject to change without notice.