

GUN OWNERS

MODELS 6024-7242
 Now Feature Both
 1 Hour Fire (1400°F)
 and U.L. RSC
 Burglary Labels
 (BF)

Protect Your Guns And Valuables From Fire or Burglary



**NEW
 MODEL
 SAFE!**



New Premium Quality Door Organizers With All Safes

Model	Outside Dimensions			Inside Dimensions			Approx. Weight (lbs.)
	H	W	D	H	W	D	
GF5517-C or E	55¼"	17¼"	16"	53"	16"	11½"	265
BGF6024-C or E	59⅞"	24"	22"	55"	21"	16"	520
BGF6030-C or E	59⅞"	30"	26"	55"	26¾"	20"	650
BGF6040-C or E	59⅞"	40"	26"	55"	37¼"	20"	805
BGF7242-C or E	72"	42"	27½"	68½"	39"	21"	882

Powder Coated Matte Finish in Black – Extremely Durable. Gold or Silver Trim Available.
 BGF6024/6030/6040/7242 safes have Group II combination locks as a standard feature. S&G Type I Electronic Lock, add \$195 Retail List.
 All Purpose (3 shelf) interiors available as an option. 4 anchoring holes with hardware included.



*"Protect Your Guns and Valuables
 and Take A Bite Out of Crime with Gardall"*

www.gardall.com



Gardall Firelined Gun Safes



MODEL GF5517
Single Layer of Fire Protection

Outside Dimensions (Inches)			Inside Dimensions (Inches)			Approximate Weight (lbs.)
H	W	D	H	W	D	
55½"	17¾"	16"	53"	16"	11½"	265
<ul style="list-style-type: none"> 3-way locking bolts – 5 active 1" bolts 3 spoke handle 4 anchoring holes in bottom S&G electronic lock available as option 11 gun slots 			<ul style="list-style-type: none"> Powder coated paint: black Safe fits in standard closet Fire tested at 1200° F for 30 minutes Add 2" to depth for handle 3-1" dead bolts on hinge side 			



MODEL BGF6024
Double Layer of Fire Protection

Outside Dimensions (Inches)			Inside Dimensions (Inches)			Approximate Weight (lbs.)
H	W	D	H	W	D	
59½"	24"	22"	55"	21"	16"	520
<ul style="list-style-type: none"> 3-way locking bolts – 7 active 1½" bolts U.L. Group II lock with spyproof dial 2 layers ½" U.L. rated fire board insulation U.L. Approved Intumescent door seal expands to 7X original size S&G electronic lock available as option 			<ul style="list-style-type: none"> 16 gun slots, 5 spoke handle 4 anchoring holes in bottom U.L. RSC Burglary Label/CA DOJ Fire tested at 1400° F for 60 minutes Add 3" to depth for handle 3 dead bolts on hinge side 			



MODEL BGF6030
Double Layer of Fire Protection

Outside Dimensions (Inches)			Inside Dimensions (Inches)			Approximate Weight (lbs.)
H	W	D	H	W	D	
59½"	30"	26"	55"	26¾"	20"	650
<ul style="list-style-type: none"> 3-way locking bolts – 7 active 1½" bolts U.L. Group II lock with spyproof dial 2 layers ½" U.L. rated fire board insulation U.L. Approved Intumescent door seal expands to 7X original size S&G electronic lock available as option 			<ul style="list-style-type: none"> 22 gun slots, 5 spoke handle 4 anchoring holes in bottom U.L. RSC Burglary Label/CA DOJ Fire tested at 1400° for 60 minutes Add 3" to depth for handle 3 dead bolts on hinge side 			



MODEL BGF6040
Double Layer of Fire Protection

Outside Dimensions (Inches)			Inside Dimensions (Inches)			Approximate Weight (lbs.)
H	W	D	H	W	D	
59½"	40"	26"	55"	37¾"	20"	805
<ul style="list-style-type: none"> 3-way locking bolts – 9 active 1½" bolts U.L. Group II lock with spyproof dial 2 layers ½" U.L. rated fire board insulation U.L. Approved Intumescent door seal expands to 7X original size S&G electronic lock available as option 			<ul style="list-style-type: none"> 39 gun slots, 5 spoke handle 4 anchoring holes in bottom U.L. RSC Burglary Label/CA DOJ Fire tested at 1400° for 60 minutes Add 3" to depth for handle 3 dead bolts on hinge side 			



MODEL BGF7242
Double Layer of Fire Protection

Outside Dimensions (Inches)			Inside Dimensions (Inches)			Approximate Weight (lbs.)
H	W	D	H	W	D	
72"	42"	27½"	68½"	39"	21"	882
<ul style="list-style-type: none"> 3-way locking bolts – 9 active 1½" bolts U.L. Group II lock with spyproof dial 2 layers ½" U.L. rated fire board insulation U.L. Approved Intumescent door seal expands to 7X original size S&G electronic lock available as option 			<ul style="list-style-type: none"> 45 gun slots, 5 spoke handle 4 anchoring holes in bottom U.L. RSC Burglary Label/CA DOJ Fire tested at 1400° for 60 minutes Add 3" to depth for handle 3 dead bolts on hinge side 			



***"Protect Your Guns and Valuables
and Take A Bite Out of Crime with Gardall"***

SAFE MANUFACTURERS SINCE 1950

