

Visit us online at www.gardall.com

MADE IN THE U.S.A.

All BF safes were tested by the manufacturer along side a U.L. listed one-hour fire safe in an independent fire testina facility. The BF safe actually outperformed the U.L. fire safe by 15 minutes. The exterior of the safe was heated to 1700°F for one hour and during that time the interior temperature of the safe was less than 270°F. A letter of certification is available upon request. All BF safes carry Gardall's Lifetime Replacement Guarantee.



Gardall's BF models provide both burglary and fire protection for your home or office application. We have been manufacturing fire safes since 1950 and the BF safe is our premier model in quality and function.

Standard Features

- Door: 1½" profile door panel with overall 4" thickness, insulated for protection against fire, with a "B" burglary rating.
- Body: 1/8" plate steel with 2½" of insulation and a metal inner shell.
- UL listed, S&G Group II combination lock

Anti Burglary Components:

- Hard plate to deter drilling.
- Independent re-locking device.
- Solid steel handle designed to shear off under attack.
- Three massive 1" round chrome plated locking bolts.
- Full length locking bar on hinge side of safe deterring prying attacks.
- One anchoring hole in base for easy bolt down. (hardware included)
- Gardall Lifetime Replacement Warranty (see inside front cover)
- Intumescent seal to ensure a positive door seal in case of fire.

Fire and Burglary Labels

- U.L. Residential Security Container Burglary Label (RSC)
- Manufacturer's 350°F 1 Hour Fire Label

Lock Options

• Electronic, Combination, Single Key Standard colors: Gardall Gray or Sandstone.

Deluxe Option

• Gold handle, dial and trim.

Optional Color: Black, hunter green, maroon



* Intumescent means an expandable door seal meant to protect your valuables from fire, smoke, and water damage.



Model	Outsid H	de Dimer W	nsions D	Insid H	e Dimen W	sions D	Cubic Inches	Approx. Weight (lbs.)	Shelves
BF1713	21¼"	18¼"	201/8"	16½"	13"	13¼"	2,842	355	1
BF2016	25¼"	21¾"	22%"	20"	16½"	15¼"	5,032	467	1
BF3318	38¼"	23"	26¼"	33"	17¼"	18"	10,246	796	2