

Experience a safer
and more open world

HES | Securitron Product Catalog



HES 7000 Series Faceplate Options



Cylindrical Locksets

Operation: After releasing the latchbolt, the keeper returns to the locked position.



4-7/8" × 1-1/4"
[123.8mm × 31.75mm]

791 Option

For use with: Cylindrical locksets up to 5/8" [15.9mm] throw

ANSI/BHMA Numbers: E09321, E09322, E09323



1
Grade 1



7-15/16" × 1-7/16"
[201.6mm × 36.5mm]

792 Option

For use with: Cylindrical locksets up to 5/8" [15.9mm] throw

ANSI/BHMA Numbers: E09321, E09322, E09323



1
Grade 1



Rim Exit Devices

Operation: After releasing Pullman latch, the keeper returns to the locked position.




9" × 1-3/4" × 11/16"
[228.6mm × 44.5mm
× 17.5mm]

783S Option

For use with: Rim exit devices in metal jambs with up to a 3/4" [19mm] Pullman latch

Compatible locksets: American Device, Arrow, Dor-O-Matic, Monarch, Precision, Sargent, Von Duprin, Yale

ANSI/BHMA Numbers: E09311, E09312, E09313



2
Grade 2




6-1/2" × 1-3/4" × 1/2"
[165.1mm × 44.5mm
× 12.7mm]

786S Option

For use with: Rim exit devices in aluminum jambs and surface mounted vertical rod exit devices with up to a 3/4" [19mm] Pullman latch. Includes keeper pocket adapter.

Compatible locksets: American Device, Arrow, Dor-O-Matic, Jackson, Monarch, Precision, Sargent, Von Duprin, Yale

ANSI/BHMA Numbers: E09311, E09312, E09313



2
Grade 2




9" × 1-3/4" × 1/2"
[228.6mm × 44.5mm
× 12.7mm]

789S Option

For use with: Rim exit devices in aluminum jambs with up to a 3/4" [19mm] Pullman latch. Includes keeper pocket adapter.

Compatible locksets: American Device, Arrow, Dor-O-Matic, Jackson, Monarch, Precision, Sargent, Von Duprin, Yale

ANSI/BHMA Numbers: E09311, E09312, E09313



2
Grade 2

"For use with" information is offered as a recommendation only. Reference should be made to the lockset manufacturer for proper installation instructions necessary to meet compatibility requirements.

HES® 7501 Electric Strike Complete Pac

*Works with cylindrical locksets
up to a 3/4" throw latchbolt*

Also available in
a Complete One
Box Solution



The Grade 1, fire rated, preload solution.

The HES 7501 Series Electric Strike is ideal for fire rated applications with preload conditions caused by a warped or misaligned door, weather stripping, a smoke seal or any other condition that could cause door bind. The heavy duty stainless steel construction provides the strength and durability required to accommodate fire rated latchbolts up to 3/4" throw.

Features

Standard Features

- Stainless steel construction
- Tamper resistant
- Static strength 1,500 lbs
- Dynamic strength 70 ft-lbs
- Endurance 1 million cycles
- Field selectable fail safe/fail secure
- Accommodates preload (up to 15lbs: fail secure only)
- Non-handed
- Internally mounted solenoid
- Strike body depth 1-11/16" [42.86mm]
- Plug-in connector
- Trim enhancer
- SecuriCare five-year, no-fault, no questions asked warranty (Addition of HES SMART Pac® III extends the warranty to 10 years)

Optional Features

- **LBM** Latchbolt monitor

Accessories

- **2001M** Plug-in bridge rectifier
- **2004M** Electrolynx® adapter
- **2005M3** SMART Pac® III
- **2006M** Plug-in buzzer
- **150** Strike latch guard
- **HES-CUT-MTK** Metal Template Kit



Grade 1



SecuriCare
Warranty



Cylindrical
Locksets



Field Selectable
(Fail secure
/ Fail safe)



Dual Voltage
12/24



Fire Rated



Preload



Burglary
Rated