


CONCEALED ELECTRIC HINGE MODIFICATION

Available in Tri-Con and Five Knuckle. Available on Ball Bearing and Antifriction Bearing hinges only. May not be available on all sizes or finishes. Contact Hager Customer Service for availability.

(For Swing Clear, Wide Throw, Half Surface, Half Mortise, Raised Barrel and Jamb Surface Mount, contact Hager Sales and Service for pricing and availability.)



CONCEALED ELECTRIC MONITOR

Miniature snap action switch is incorporated into the frame leaf. Available in 4" through 8". Full mortise ball bearing hinges.

NRP NOT NECESSARY AS HINGES ARE CROSS PINNED AND ARE NOT FIELD REMOVABLE.
To order use symbol EMN as suffix.

CONCEALED ELECTRIC THROUGH-WIRE

Four continuous electric conductors (28 gauge wire)

Available in 4" through 8".

Full mortise ball bearing, standard weight and heavy weight in steel and brass material.

NRP NOT NECESSARY AS HINGES ARE CROSS PINNED

AND ARE NOT FIELD REMOVABLE.

To order use symbol ETW as suffix.

ETW-4 (4 wire)


ETW-6 (6 wire)

ETW-8 (8 wire)

ETW-10 (10 wire)

ETW-12 (12 wire)

CONCEALED ELECTRIC THROUGH-WIRE & MONITOR



Full mortise ball bearing, standard weight and heavy weight in steel and brass material. NRP NOT NECESSARY AS HINGES ARE CROSS PINNED

AND ARE NOT FIELD REMOVABLE.

To order use symbol **ETM** as suffix.

ETM-4 (4 wire)

ETM-6 (6 wire)

ETM-8 (8 wire)

ETM-10 (10 wire)

ETM-12 (12 wire)

The hospital tip feature is available on concealed electric hinges.

STANDARD WIRE LEAD - 8" PER SIDE: 28 GAUGE WIRE Additional Wire Leads—must be bought in 4, 8, & 12 foot lengths

ELECTRIC HINGE REPAIR