

How to Order GTS-STP

Heavy-Duty Grade 1 Cylindrical Lock

QTY	SERIES	FAMILY	FUNCTION	TRIM	FINISH	HANDING	BACKSET	STRIKE	CYLINDER	KEYWAY	KEYING	OPTIONS
	GTS	STP	116	PHL	626	RH	234	ASA	D	SCC	KD	—
				BSN	606	LH	234 - 2-3/4" (default)	ASA - ANSI/ASA (default) FL - Full Lip T - "T" Strike	D - Default L - Less Cylinder SF6 - SFIC w/ Core, 6 Pin SF7 - SFIC w/ Core, 7 Pin LF - Schlage® Compatible LFIC w/Core SFL - SFIC Housing less core LFL - Schlage® Compatible LFIC Housing less core55	AR1	KD - Keyed Different	TC10S - Tactile Abrasive Coating - Outside only TC2 - Tactile Abrasive Coating - Both Sides SF - Split Fin- ishes LL - Lead- Lined Rose DB - Dust Box AM - Antimicrobial Coating
			MIA	612		C059A1				KO - Zero Bitted		
				613		C06				KA - Keyed Alike		
				622		CL4				KE - Keyed to Existing		
									RUD	MK - Master Key		
									SCE	CMK - Construc- tion Master Key		
									SCC			
									SCC-K			
									SAL			
									RA-RC			
									YA8			
									GA			
									FAL			
									KW			
									TA			
									A (Best Keyways)			
									PDQ1			
									PDQ2			
									PDQ3			

