



**114XY Full mortise - narrow frame leaf, door edge protector**

- For 1 3/4" doors
- Door edge protector
- Recommended for gasketing and weatherstripping applications
- Patented center loaded, interlocking bearing design
- Non Handed for custom cut lengths
- 1/16" door inset
- 48" Maximum door width
- Beveled or square edge doors
- Frame guidance lip is extended further for retrofit applications to cover existing heavy weight architectural hinge preps
- For doors weighing up to 450 pounds without reinforcing, 600 pounds with reinforcing
- For lead-lined application consult factory for engineering specials

**Certifications**

- Meets ANSI 156.26 for 150lbs and 300lbs
- UL10C certified

**Standard lengths**

- 83", 85", 95", 119"

**Standard mounting hardware**

- 12-24 x 3/4" Steel self drilling / self tapping phillips head screw

**Finishes**

- Clear Anodized (US28), Dark Bronze Anodized (313AN), Black Anodized (315AN)
- Custom anodizing and painting are available, consult factory.

**Options:**

- HT.....Hospital tip
- EPT.....Electric power transfer
- TWP CON.....Electrical through wire panel with Allegion Connect

**Optional mounting hardware:**

- SECHM.....Security screws - hollow metal door and frame
- SECWDHM.....Security screws - 1/2 wood, 1/2 hollow metal
- SECWDWD.....Security screws - wood door and frame
- TEKWD.....1/2 self drill, self tap 1/2 wood
- WD.....Wood door and frame

**For single door applications:**

For pairs of doors see chart and general information

