LOCKING LADDER PULL - FULL HEIGHT PULL ORDER FORM

ORDER DATE CUSTOMER N CUSTOMER P FINISH: QUANTITY: CUSTOMER SI	JAME: :O. #:					
ALLFH-BD (BOLT DOWN ALLFH-BU (BOLT UP) ALLFH-BD/BU (BOLT						Γ DOWN/UP)
FINISH:	US32D	US32	US3	US4	US10	US10B
	CUSTOM POV	WDER COAT:				
TOP MOUNTING POST CTC (LOCK POST) A: TOP MOUNTING POST CTC (LOCK POST) B: OVERALL PULL LENGTH: DOOR TYPE: GLASS METAL WOOD DOOR THICKNESS: POST END TO MOUNTING POST CENTER: (TYPICALLY 6")						
LOCK END TO MOUNTING POST CENTER: (TYPICALLY 2-3/4")						
- 02-SF	N TYPE: ST YPE: TOCK CONSTI FIC HOUSING	JSH PU TANDARD RUCTION COR (STANDARD) PPLIED HOUS	ADA RE		C	MOUNTING POST BOLT

NOTE: CYLINDER MUST BE LOCATED 34"-48" ABOVE FINISHED FLOOR TO MEET ADA REQUIREMENTS. CALIFORNIA ADA REQUIRES CYLINDER TO BE LOCATED 36"-46" ABOVE FINISHED FLOOR.



E-mail: <u>sales@fcbp.com</u> First Choice Building Products, LLC. 1222 Ardmore Avenue, Itasca 60143 800-793-4544 • FAX 800-867-5016 • <u>www.fcbp.com</u>

- Download File
- Fill out Form & Save

BOLT

- SUBMIT
- Attach File & Send



FCBP Locking Ladder FULL Height Pull Order Form 012723