

MRXA-Heavy Duty Ligature Resistant Mortise



MRXA-05 (OUTSIDE)

- Schlage® LFIC less core available
- Corbin® LFIC less core available
- High security cylinder available, TownSteel “L” keyway, 6 pin
- High security SFIC core available, TownSteel “L” keyway, 7 pin
- KD, KA, MK, GMK, GGMK and construction keying available
- Available functions: F-01, 02, 04, 05, 07,13, 22, 26, visit townsteel.com for more available functions
- Available finish: US32D
- Patent pending design
- 10-year Manufacturer’s Limited Warranty

Specification

- ANSI Grade 1 heavy duty mortise lock with 5-point ligature resistant arch trim
- Backset 2-3/4”
- Door thickness: 1-3/4” standard, other upon request
- Stainless steel arch trim
- Stainless steel latch bolt, split, anti-friction, 3/4” throw
- Stainless steel dead bolt, with anti-saw pins, 1” projection
- Stainless steel ADA thumb turn standard
- Stainless steel ANSI strike
- Tamper resistant stainless steel mounting screws
- Handed
- Schlage “C” keyway, brass 6 pin cylinder standard
- SFIC with or less core available, 6 or 7 pin core

Code Compliance

- ANSI/BHMA Certified A156.13-2005 Grade 1 Certified
- UL 10C Listed 3-Hour Fire Rating
- Meets requirements of The Buy American Act
- Meets requirement of The Americans with Disabilities Act

Important Note:

It is TownSteel’s position that if any of our keyed locks are to be used less cylinder, whether I.C. or standard, and another manufacturer’s cylinder is to be used in place of the TownSteel original manufacturer’s cylinder, that a sample of that product be provided to TownSteel in advance for testing.

