



714-772-5202 FAX 714-772-2302

web: [www.majormfg.com](http://www.majormfg.com)

### INSTRUCTIONS FOR USE WITH HIT-118 INSTALLATION TOOL FOR ALARM LOCK TRILOGY

Remove allen bolt and back plate. Place HIT-118 drill guide on door with aligning washers in the 2-1/8" crossbore. HIT-118 should be placed on door so the writing on the front plate is in the upright position. Replace back plate and tighten allen bolt until snug. Do not over tighten. HIT-118 is now ready to retrofit Alarm Lock T2, T3 and T3 Prox cylindrical locks. All through bolt holes may be drilled in one operation through the door, or half way from both sides. This unit was designed to retrofit locks with 2-3/4" backsets. The use of this fixture for 2-3/8" backsets may be accomplished the following way. Mount the template to the door as usual (the tool will over hang the door edge 3/8"). Next with the use of a combination square, square the template to the door and tighten the allen bolt. The template is now in proper alignment for use.

1. Drill two 3/8" holes through door using top two bushings of the drill guide. These are the upper through bolt holes.
2. Drill a 1/4" hole through the door using the bushing located in the center of the drill guide. **After all holes are drilled** and HIT-118 has been removed from door, re-drill this hole to 1" with the use of a hole saw. This is the wire run hole.
3. Drill two 3/8" holes through door using the bushings, located at the top and bottom of the lever handle. At the same time drill two 5/32" holes to a depth of 1/8" minimum using the bushings located at the 3 and 9 o'clock positions around the lever handle.
4. All pilot holes are now completed. Remove drill guide from the door and re-drill holes to size as noted above.
5. Install lock per manufacturer's directions. Check for proper operation when installation has been completed.



**ALWAYS WEAR EYE  
PROTECTION WHEN USING  
POWER TOOLS**