



714-772-5202 FAX 714-772-2302

web: [www.majormfg.com](http://www.majormfg.com)

**INSTRUCTIONS FOR USE WITH  
HIT-134 INSTALLATION TOOL  
FOR CODELOCK 5000**

Remove allen bolt and back plate. Place HIT-134 drill guide on door with aligning washers in the 2-1/8" crossbore. HIT-134 should be placed on door so the writing on the front plate is in the up right position. Replace back plate and tighten allen bolt until snug. Do not over tighten. HIT-134 is now ready to retrofit Codelock 5000 series locks.. All through bolt holes may be drilled in one operation through the door, or half way from both sides. This unit was designed to retrofit locks with 2-3/4" backsets. The use of this fixture for 2-3/8" backsets may be accomplished the following way. Mount the template to the door as usual (the tool will over hang the door edge 3/8"). Next with the use of a combination square, square the template to the door and tighten the allen bolt. The template is now in proper alignment for use.

**NOTE: THIS DRILL GUIDE WAS DESIGNED TO RETROFIT AN EXISTING 2-1/8" CROSSBORE. The three 10mm holes and one 25mm hole shown on the manufacturers paper template will be inside the 2-1/8"crossbore.**

1. Drill two 3/8" holes through door using the bushings located at the top of the HIT-134 drill guide. These holes can be drilled through from one side of the door or half way from both sides. This hole is for the top mounting screws
2. Drill one 1/4" hole through door using the bushing located in the center of the drill guide. After all holes are drilled and the HIT-134 is removed from the door, enlarge this hole to 1" using the 1/4" hole as a pilot for a hole saw.
3. Install the Codelock 5000 lock as per directions provided by the manufacturer.



**Drill two 3/8" holes through door**



**Drill 1/4" hole through door and enlarge to 1" with a hole saw.**

**ALWAYS WEAR EYE  
PROTECTION WHEN USING  
POWER TOOLS**