

Notes:

- 1. Do not scale drawing.
- 2. Dimensions are given in inches (mm).
- 3. All lead furnished by others.
- 4. Right hand shown.
- 5. Template drawing for reference only.

Door Size	"A" Dim.	"B" Dim.	Max. Lead Thk.
1-3/4 (44.5)	1-1/4 (31.8)	1/4 (6.4)	9/32 (7.1)
2 (50.8)	1-3/8 (35)	5/16 (7.9)	3/8 (9.5)
2-1/4 (57.2)	1-1/2 (38.1)	3/8 (9.5)	15/32 (11.9)
2-1/2 (63.5)	1-5/8 (41.3)	7/16 (11)	9/16 (14.3)
3 (76.2)	2 (50.8)	1/2 (12.7)	3/4 (19)

- For door thicknesses not listed, use next size smaller for prep.
- Table above is based on the assumption that lead is place in center of door.

L180 Top Pivot 3/4" Offset For High Traffic, Heavy or Lead Lined Doors

RIX	SC	N
ASSA	ABL	.OY

www.rixson.com


TEMPLATE NUMBER


REV DATE 3 05-24

L180 Top Pivot


Location


Attachment






- 1. Attach door leaf of top pivot to door.
- 2. Attach jamb leaf of top pivot to frame.
- 3. If side jamb pivot is used, see required template for instructions.
- 4. Push top pivot pin into place. Tighten set screw.
- 5. Attach pivot cap. CAP MUST BE TIGHTENED SECURELY.







Face a door swinging open away from you. If it opens to the right, it is right hand. If it opens to the left, it is left hand.

L180 Top Pivot 3/4" Offset For High Traffic, Heavy or Lead Lined Doors RIXSON° ASSA ABLOY

www.rixson.com

IS-L180

REV I

05-24