722S | 722S-TBM

SFIC: Sliding Door **Plunger Lock**



core cylinders

SPECIFICATIONS

Retrofits: Best 2S, 2S-TBM

Standard function: Key removable in locked and

unlocked position.

Key-retaining function: Key removable in locked position only. Specify -KR for key-retaining. TBM function: Specify TBM for "through-bolt

mounting" **Body:** Solid brass

Barrel length: 1-3/4" Bolt throw: 1/2"

Max. door thickness: 1-7/8" Min. door thickness (TBM): 5/8"

Finish: 26D

Packaged: Packed 10 per box

KEYING INFORMATION

Cores: Not included

Accepts: Best, Arrow, Falcon, KSP, Schlage SFIC or equivalent small format interchangeable cores Compatible electronic cylinders: Medeco Nexgen XT or VIDEX CyberLock SFIC cylinders

INCLUDED ACCESSORIES

725-1 spacer to fit 6 or 7 pin cores Matching strike 725-PA plastic thumbturn TBM locks include through-bolt plates and screws

OPTIONAL ACCESSORIES

SFIC cores: 206/207 Series



722S

Function: Sliding door plunger lock for

bypassing sliding doors

Material: Fits up to 1-3/4" material Standard function: Key removable in locked or unlocked position. Standard

locks are non-handed.

Key-retaining function: Key removable in locked position only. Specify -KR for

key-retaining.



722S-TBM

Function: Sliding door plunger lock for bypassing sliding doors. Includes with through-bolt mounting hardware. Material: Fits up to 1-3/4" material Standard function: Key removable in

locked or unlocked position. Standard locks are non-handed.

Key-retaining function: Key removable in locked position only. Specify -KR for

key-retaining.





722S | 722S-TBM

SFIC: Sliding Door Plunger Lock

OPTIONAL ACCESSORIES - See our website for a complete list of optional components.


206/207 Series


- 206 Series 6-pin SFIC cylinder
- 207 Series 7-pin SFIC cylinder







AVAILABLE KEYWAYS									
	5	>	Ş	7	>	5	>	5	
	Α	В	C	D	E	F	G	н	
	}	7	7	7	}	5	5	}	
	J	к	L	м	0	10	1D	KMT300	









DIMENSIONS

