# **DCR SERIES**

R Series: 3/4" Cam Lock

## ANSI/BHMA Grade 1 E07261 | E07271

Woodwork Institute (WI) acknowledged product

### **SPECIFICATIONS**

**Keying:** Can be keyed together with other

R Series locks

Cylinder length: DCR1 =1", DCR2=1-1/8",

DCR3=1-3/8" and DCR4=1-3/4"

Rekeyable: Easily rekeyable via cylinder retainer clip

ANSI/BHMA: Passed ANSI/BHMA A156.11

Grade 1 performance requirements. Equivalent to

E07261 / E07271.

**US Patent Nos:** 5,038,589; 5,737,950

Body: Zinc die cast

Cylinder: Zinc die cast, pin tumbler

Standard function: Key removable in locked or

unlocked position.

**Key retaining function:** Alternate key-retaining shifters are available separately for key removable

in locked position only.

**Cams:** 2 reversible cams work in all positions **Face:** 1" face covers splintering, no additional trim

ring required Finish: 26D or US3

Packaged: Packed 10 per box

#### **KEYING INFORMATION**

**Keyway:** R Series (equivalent to CCL R1 system)

Keys: Includes 2 keys per lock Stock keying: KD/KA - 5 pin standard Stock KA#: 4T21579, 4T37526 Masterkeyed: 5 pin standard Grand masterkeyed: Available Keyblank 5-pin: KBR-5-NP (equivalent to CO106, 1003A)

#### **INCLUDED ACCESSORIES**

See below.

#### **OPTIONAL ACCESSORIES**

Alternate cams

Key retaining drawer cam shifter #DCNP-200-KR Key retaining door cam shifter #DCNP-200-KDR

## **DCR**

**Keyway:** R Series, CCL R1 Keyway **Handing:** Includes 2 cams that work all handings (door or drawer)

#### **DCR SERIES FEATURES**

- Non-handed—Field reversible locking positions: right-hand, lefthand, vertical and inverted
- Only 2 cams required—Ships with reversible straight and offset cams that meet requirements of all locking positions
- Easy rekeyability—Allows for a quick installation and increased productivity



 Anti-rotation plate—Eliminates lock rotation, prevents loosening of fixing nut, and provides additional security in particleboard applications

### **AVAILABLE FINISHES**







US26D

US3

#### **INCLUDED CAMS**







**DCNP-100-BC** offset reversible cam



WARNING: This product can expose you to chemicals including chromium, which is known to the State of California to cause cancer and birth defects or other reproductive harm. For more information go to www.P65Warnings.ca.gov.



# DCR SERIES

R Series: 3/4" Cam Lock

# ANSI/BHMA Grade 1 E07261 | E07271

Woodwork Institute (WI) acknowledged product

# **OPTIONAL ACCESSORIES** - See our website for a complete list of optional components.

### Other Accessories

### Key-retaining cam shifters

- For door function: DCNP-200-KDR
- For Drawer function: DCNP-200-KR

#### Washers

- Pronged wood washer: DCNP-SPW
- Self-adhesive clear plastic washer for mounting lock on glass: DCNP-GW

### **Finger Pull**

Finger pull: DCNP-300-FP

### **Number Plates**

T37DC-NP number plate





self-adhesive clear plastic washer for mounting lock on glass

### **TRB7 Series Trim Collars**














## **Optional Cams**

**Note:** Offset cams are reversible and can be used in either the inbent or outbent position.


Item	Description / Packed Each	
DCNP-HD-875	7/8" long straight cam	
DCNP-HD-1	1" long straight cam	
DCNP-100-SC	1-1/4" long straight cam	
DCNP-100-SC2	1-3/4" long straight cam	
DCNP-100-SC3	1-1/2" long straight cam	
DCNP-100-LC	3" long straight cam	

Item	Description / Packed Each	
DCNP-100-B1	Straight cam with oval cutout	
DCNP-100-B2	U-shaped cam	
DCNP-100-B3	Straight hook cam	
DCNP-100-WB	Short cam / 90° offset arm	

Item	Description / Packed Each		
DCNP-100-BC	1-1/4" long cam, 5/16" offset		
DCNP-100-BC5	1-1/4" long cam, 1/2" offset		
DCNP-100-HC1	1-1/2" long hook cam, 5/16" offset		
DCNP-100-HD	1-7/16" long cam, 1/2" offset		
DCNP-100-HD2	1-3/4" long cam, 5/16" offset		
DCNP-100-HD3	1-1/8" long cam, 5/16" offset		
DCNP-100-LBC	1-1/2 long cam, 5/16" offset		

>> Visit our website www.olympuslock.com for complete dimension and descriptions of available optional cams.

# **DIMENSIONS | TYPICAL INSTALLATION**



### **DIMENSIONS**

	For Mat. Thickness	Straight Cam (X)	Inbent Cam (Y)	Outbent Cam (Z)	Cylinder Length (A)
DCR1	3/4"	1-1/16"	3/4"	1-3/8"	1"
DCR2	7/8"	1-3/16"	7/8"	1-1/2"	1-1/8"
DCR3	1-1/8"	1-7/16"	1-1/8"	1-3/4"	1-3/8"
DCR4	1-1/2"	1-13/16"	1-1/2"	2-1/8"	1-3/4"

### **MOUNTING CUTOUT**

