

## EXIT DEVICES



# PD21 Series

- **MOTORIZED NARROW STILE GRADE 1 EXIT DEVICE**
- **QUIET, FAST, SMART & STRONG LATCH RETRACTION – ELECTRONIC DOGGING**
- **COMPARABLE TO THE VON DUPRIN 33/35 RIM & SVR SERIES**
- **UL/CUL LISTED: LISTING FOR PANIC EXIT HARDWARE AND 3 HOUR RATING FOR FIRE EXIT HARDWARE**
- **ANSI/BHMA CERTIFIED: DEVICES ARE A156.3 GRADE 1.**



The **Command Access PD21 series** is a motorized latch pullback Grade 1 narrow stile architectural exit device; made for use on contemporary glass aluminum doors. They may also be used on wide stile doors for an appearance on institutions and commercial buildings when heavy-duty, fire, and life safety operation is required. All PD21 models come equipped with our PTS “push to set” technology. We know that door conditions change, especially in retrofit scenarios. However, with our PTS adjustment, your post-installation adjustment is greatly simplified in 5 quick seconds. Install this device with the confidence of knowing that the 21 meets or exceeds the high standards of another grade 1 product and carries our 3-Year “No-Hassle“ Warranty, meaning we support you.

## FEATURES

- Our motorized latch retraction is fast, quiet, and smooth!
- MM4 Smart Module: On board diagnostics with audible feedback for adjustment and power issues
- “PTS”: 5 second electronic adjustment for easy post installation adjustment
- Electric dogging rated for continuous duty - Auto re-engage if pulled from the dogged position
- Low current draw: Compatible with most 24VDC, 1A (or greater) regulated & linear power supplies
- Up to 300’ with 2-18ga --Long wire runs with provides installer with convenience of placing the locking device power supply in a centralized location; i.e. the same closet as the access panel
- 8’ cable with Quick Connect for MM4 module to easily connect to power supply lead
- The slim, compact attractive low profile design enables mounting on narrow-style doors.
- 3-year “no hassle” warranty - Longer than the traditional 1 year warranty because our stuff works!

## ACCESSORIES - Additional charges

- Request to Exit (REX) - Switch available factory installed
- Request to Exit Kit (PD21REXKIT-M-ED) - Switch available for installation in the field

## FINISHES

- US26D

U.S. Customer Support  
1-888-622-2377

Visit our website for more details  
[www.CommandAccess.com](http://www.CommandAccess.com)

Canada Customer Support  
1-855-823-3002

Command Access is not a licensee, or affiliated, associated or connected with Allegion, Assa Abloy, Stanley, Schlage, Falcon, Von Duprin, Dorma, Sargent, Corbin Russwin, Yale, Emtek, Adams Rite, Best, Precision, Arrow, Design Hardware, Cal Royal, Jackson, Kawneer, AHT, Marshall Best, Marks, Accurate, Baldwin, FSB, PDQ, Lawrence, Trans Atlantic, Hager, LSDA, General Lock, or Omnia or any of their subsidiaries or affiliates.

# SPECIFICATIONS



## **Voltage**

Range - 24 to 28VDC

System Protection - Unit shutdown when voltage exceeds 28VDC

Standard - Average Current Peak: 900MA

Average Current Hold: 215MA

PTS Adjustment – Approx. 1/4”

## **Device Lengths**

Short (36”) actual end to end length 33-1/2” (850mm)

Long (48”) actual end to end length 45-1/2” (1137mm)

## **Cutdown Details**

36”/ 48” - 6.5” Filler Plate Needed

## **Minimum Stile Width**

2-19/32” (66mm)

## **Door Height**

Our standard and fire rated vertical rod exit device accommodates up to 8’ (2438mm) doors.

Fire rated devices may be ordered for up to 10’ (3048mm) fire exit doors. Specify door height if greater than standard sizes when ordering.

Note: For fire rated devices consult door manufactures literature for maximum allowable door height and width.

## **Latch Bolt**

3/4” (19mm) throw, deadlocking design

## **Strikes**

801 (Panic), 802 (Fire)

## **Dogging**

Fire Exit device - No Dogging (ND)

## **Dogging Options**

Less Dogging (LD)

## **Fasteners**

Panic Device - Machine screws furnished standard.

For wood doors sex nuts and bolts (SNB) can be ordered separately

Fire Exit Device - Sex nuts and bolts (SNB) supplied standard

## **Mounting Height Projection**

Standard device centreline from finished floor is 40” (1016mm)

Push bar Neutral 3-1/16” (78mm). Push bar





Depressed 2-19/32” (66mm)

## **Certification**

UL/cUL Listed: Listing for Panic Exit Hardware and 3 Hour rating for Fire Exit Hardware ANSI/

BHMA Certified: Devices are A156.3 Grade 1.

## ET22 Series Exit Trim

<b>Operations Options</b> (Dummy trim is not recommended for fire rated devices)  <b>L6 Standard Lever Shown</b>	Key Locks and Unlocks Lever  	Lever Always Active (no Cylinder)  	Key Retracts Latchbolt (Rigid Lever)  	Pull When Device Dogged (Rigid Lever)  
<b>Function</b>	Entrance	Passage	Storeroom	Dummy
<b>Trim Designation</b>	Cylinder Escutcheon Lever	Blank Escutcheon Lever	Night Latch Escutcheon Lever	Dummy Escutcheon Lever
<b>Model Number and Uses</b>	For Rim, Surface / Concealed Vertical Rod and LBR			
	ET22ELT	ET22PLT	ET22SLT	ET22DLT
<b>ANSI Function Number</b>	8	14	3	2
<b>Cylinder Type</b>	Mortise	Not Required	Rim	Not Required



L3



L6



L17

## How to Order

PART #	EASY ORDER #	DESCRIPTION
PD21-M RIM 626 36"	72403	Narrow Stile Rim Exit Device. 36" 626.
PD21-M RIM 626 48"	72606	Narrow Stile Rim Exit Device. 48" 626.
PD21F-M RIM 626 36"	72610	Narrow Stile Rim Fire Rated Exit Device. 36" 626.
PD21-M SVR 626 36"	79696	Narrow Stile SVR Exit Device. 36" 626.
PD21F-M SVR 626 36"	72611	Narrow Stile SVR Fire Rated Exit Device. 36" 626.
PD22 RIM 626 36"	72609	Narrow Stile Rim Exit Device. 36" 626.
PD22 SVR 626 36"	79695	Narrow Stile SVR Exit Device. 36" 626.

### NEED A LOCKING HARDWARE POWER SUPPLY?

RECOMMENDED LOCKING HARDWARE POWER SUPPLIES:

- PS204/PS204B
- PS210
- PS220/PS220B
- PS440B
- PS480B

