

# 6300R - PANIC & 6300RF - FIRE LABELED RIM EXIT DEVICES WITH 639027 PANIC OR 639057 FIRE STRIKE

TEMPLATE: 639301

REV. 1 04/14/22

## 6300 SERIES EXIT DEVICES USING SNB OR SURFACE MOUNT FASTENERS

### DEVICE

**MACHINE SCREWS:**  
USE #7 OR 13/64" DRILL AND 1/4-20 TAP

**WOOD SCREWS:**  
USE 5/32" DRILL

**SEX NUTS:**  
USE 3/8" DRILL PULL SIDE  
USE 9/32" DRILL PUSH SIDE

### STRIKE

**MACHINE SCREWS:**  
USE #25 OR 5/32" DRILL AND #10-24 TAP

#### NOTES:

1. VERIFY PRINTED TO SCALE
2. SEX NUTS MAY BE REQUIRED FOR UNREINFORCED DOORS OR COMPOSITE FIRE DOORS. CONSULT DOOR MANUFACTURER'S RECOMMENDATIONS
3. SEE TRIM TEMPLATE (IF APPLICABLE) FOR RELATED MACHINING DETAILS
4. DIMENSION "X" SIZED FOR DOOR. REFER TO DEVICE INSTRUCTIONS WHEN CUTTING DOWN FOR NARROWER OPENING
5. CHECK PDQ WEBSITE FOR MOST RECENT REVISION [WWW.PDQLOCKS.COM](http://WWW.PDQLOCKS.COM)
6. MINIMUM STILE WIDTH: 4 1/4"

