

6300R - PANIC RIM EXIT DEVICES WITH BLADE STOP STRIKE ON AL STOREFRONT

TEMPLATE: 639319
REV. 0 1/22/22

DEVICE	
MACHINE SCREWS:	USE #7 OR 13/64" DRILL AND 1/4-20 TAP
WOOD SCREWS:	USE 5/32" DRILL
SEX NUTS:	USE 3/8" DRILL PULL SIDE USE 9/32" DRILL PUSH SIDE

STRIKE

MACHINE SCREWS:
USE #25 OR 5/32" DRILL AND #10-24 TAP

NOTES:

1. VERIFY PRINTED TO SCALE
2. SEX NUTS MAY BE REQUIRED FOR UNREINFORCED DOORS OR COMPOSITE FIRE DOORS. CONSULT DOOR MANUFACTURER'S RECOMMENDATIONS
3. SEE TRIM TEMPLATE (IF APPLICABLE) FOR RELATED MACHINING DETAILS
4. DIMENSION "X" SIZED FOR DOOR. REFER TO DEVICE INSTRUCTIONS WHEN CUTTING DOWN FOR NARROWER OPENING
5. CHECK PDQ WEBSITE FOR MOST RECENT REVISION WWW.PDQLOCKS.COM
6. MINIMUM STILE WIDTH: 3 1/2"

