

6400R - PANIC & 6400RF - FIRE LABELED NARROW RIM EXIT DEVICES FOR HVHZ

TEMPLATE: 639323
REV. 0 3/01/22

6400 SERIES EXIT DEVICES USING SNB OR SURFACE MOUNT FASTENERS

The diagram shows a side view of a door strike assembly. Key dimensions include a total width of 40" [1016], a central strike width of 2 1/8", and a distance of 2 7/16" from the center to the edge. A vertical dimension of 7 1/16" is shown for the strike body, with a 7/8" gap to the door edge. A horizontal dimension of 1 13/16" is marked from the door edge to the strike body. A circular hole is labeled 'OPTIONAL Ø 1-1/4" PULL SIDE FOR CYLINDER ONLY'. A central circular feature is labeled 'DRILL AND TAP AFTER STRIKE ADJUSTMENT'. A note indicates 'FOLD HERE' at the top. A note on the right says 'VERIFY THESE AGAINST TRIM TEMPLATE THIS SIDE UP FOR LHR DOOR'. A note at the bottom right says '"X" MUST BE MODIFIED TO FIT (SEE NOTE # 4)'. A note at the bottom left says 'PUSH SIDE FACE OF DOOR'. A note at the bottom center says 'Ø1/2" ONLY FOR ELECTRIFIED OPTIONS'. A note at the bottom right says '3/8" 1 1/8"'. A note at the bottom left says 'WOOD RHR FOR PDN EDIS SIHL'. A note at the bottom center says '3/8" DEEP PUSH SIDE 7"'. A note at the bottom right says '1/4" LHR 1/4" RHR'. A note at the bottom left says 'THIS SIDE ON FRAME STOP THIS SIDE ON DOOR'. A note at the bottom center says '1 1/4" TO STOP (2 1/4" BACKSET WITH 5/8" STOP & 1/8" DOOR GAP)'. A note at the bottom right says 'FINISHED FLOOR'.