



GRADE 2

Security of a Deadbolt and Lever in One Assembly

- Field selectable prep — 4” and 5-1/2” hole centers
- CL and SD cylindricals share common levers. Match them for entry and interior doors to achieve a coordinated look.

Product Specifications



FOR DOORS:	• 1-3/8” and 1-3/4” thick.
PREPARATION:	• ANSI/BHMA A156.115 for 4” and 5-1/2” hole centers
DUST BOX:	• Included for Latchbolt and Deadbolt.
LATCHBOLT BACKSET:	• 2-3/8” and 2-3/4” (Default). Specify when ordering
DEADBOLT BACKSET:	• Field adjustable for 2-3/8” and 2-3/4” (Default).
STRIKE:	• “T”-Strike (Default). • ASA or Full-Lip optional
ROSE:	• 2-3/8” Round Rose, 2-15/16” Square Rose
INSIDE ESCUTCHEON:	• 3-3/4”W x 9-3/4”H (Wrought)
LATCHBOLT:	• 1/2” Throw
DEADBOLT:	• 1” Throw
THUMBTURN:	• ADA Compliant
HANDING:	• Non-handed (Except for Memphis Lever)
KEYING:	• Keyed to your needs , Keys, keyway, IC core, cylinder and keying information on pages 36-37.
FINISHES:	• 605 (US3) Bright Brass, 613 (US10B) Oil Rubbed Bronze, 622 (US19) Flat Black, 626 (US26D) Satin Chrome
CASE QUANTITY:	• 6 locksets
WARRANTY:	• Two (2) year Limited Warranty

Listings and Certifications

CERTIFICATIONS,	• ANSI/BHMA 156.12, Grade 2
LISTINGS,	• UL/CUL 10C listed for 3 hrs, for single doors up to 4’0” x 8’0”
COMPLIANCES:	• Complies with ADA (Americans with Disabilities Act) and ICC/ANSI 117.1 for Accessible and Usable Buildings

Levers/Trim



Finishes

