

Pemko Acoustic Thresholds

Reduces Sound Transmission for Quieter Spaces

Pemko Acoustic Thresholds assist with sound attenuation, helping to muffle the sounds that travel through a closed door. Acoustic thresholds are especially useful in areas where noise levels are different, such as a door from a factory to a conference room, or from a music classroom or theater to the hallway.


Pemko Acoustic Thresholds can help door assemblies meet ANSI Standard S12.60-2002, Acoustical Performance Criteria, Design Requirements and Guidelines for Schools. This can help school projects earn LEED IEQ School Specific Credits for Enhanced Acoustical Performance.

Features	Benefits
Extensive acoustic testing using these TPE and PK gaskets	Reduces sound transmission
6063-T6 aircraft aluminum	Durability and long lasting
Meets ANSI Standard S12.60-2002	Help to earn LEED Credits
Meets ANSI/BHMA A156.21-2014	Proven quality

Applications:

- Theaters, Auditoriums, Assembly Halls
- Sound Stages and Production Areas
- Conference Rooms
- Office Buildings

Copyright © 2012-2019,
ASSA ABLOY Accessories and
Door Controls Group, Inc.



The ASSA ABLOY Group is the global leader in access solutions. Every day, we help billions of people experience a more open world.


Acoustic Solutions

Pemko Acoustic Thresholds are just one part of a complete acoustic solution. ASSA ABLOY offers a wide range of Pemko perimeter gasketing, door bottoms and thresholds designed to assist with sound attenuation. In addition ASSA ABLOY Group companies can provide the other elements of the overall solution with STC Rated doors and frames.

Acoustic Thresholds


Available Products		
Part number	Width	Finishes
2006STC	5"	A - Mill Finish Aluminum D - Dark Bronze Anodized
2007STC	3 5/8"	A - Mill Finish Aluminum D - Dark Bronze Anodized
2008_PK	4"	A - Mill Finish Aluminum D - Dark Bronze Anodized

AVAILABLE FINISHES: A, D




2007STC

AVAILABLE FINISHES: A, D



2008_PK

AVAILABLE FINISHES: A, D



Technical Specifications:

Threshold Material:

6063-T6 Aircraft Aluminum

Finishes:

Mill Finish Aluminum, Dark Bronze Anodized

Gasket Material:

Black ThermoSeal (STC) or Black PemkoPrene (PK)

Fasteners:

#10 x 1" sheet metal screws included. Other fastener options are available upon request at an additional charge.

Sound Rated:

Tested in accordance with ASTM E 90-2009. Standard. Tested to meet ANSI Standard S12.60-2010, Acoustical Performance Criteria.

Fire Rated:

Meets UL10C Standard as a Category J gasket.

Air Infiltration:

Air infiltration tested in accordance with ASTM E283-04.

ADA Compliance:

2008_PK meets the barrier free requirements of ICC/ANSI A117.1-2009. 2006STC and 2007STC are only ADA compliant when installed butted to other flooring materials in accordance with ADA guidelines.

ANSI/BHMA:

Meets the requirements of ANSI/BHMA A156.21-2014 Thresholds.

GREENGUARD Gold Certification:

Meets the product certification requirements for low chemical emissions of UL 2818 to Gold Status.



ASSA ABLOY is a member of the USGBC and CaGBC. U.S. Green Building Council logo is a trademark owned by the U.S. Green Building Council and is used with permission.

ARCHITECTURAL DOOR ACCESSORIES™

Markar | McKinney | Pemko | Rockwood

ASSA ABLOY Opening Solutions
Architectural Door Accessories
5535 Distribution Drive, Memphis, TN 38141
orders.pemko@assaabloy.com
www.assaabloydooraccessories.us

Memphis, TN USA
P: 800 824-3018
F: 800 243-3656

Ventura, CA USA
P: 800 283-9988
F: 800 283-4050

Vaughan, ON CA
P: 800.461.3007
F: 800.461.8989