# Architectural Door Accessories



Experience a safer and more open world

# Pemko Thermal Barrier Latch Track Saddles

# **Energy Efficient and ADA Compliant**

Pemko Aluminum Thermal Barrier Latch Track Saddles provide energy savings and comply with ADA requirements.

The Thermal Barrier Latch Track Saddle helps reduce the transfer of temperature through the threshold, thereby saving on heating and cooling costs. Using both a rigid polypropylene thermal break and a gasket provides two different barriers to prevent or minimize the transfer of heat and cold. This is ideal for exterior door openings as well as cold storage rooms.

With a maximum height of  $\eta_2$ ", these latch track saddles are also specially designed to meet ADA Accessibility Guidelines for Buildings and Facilities and the ICC/ANSI A117.1 Accessible and Usable Buildings and Facilities standards.

Available in 4 width options and 3 options for gasket inserts, the Thermal Barrier Latch Track Saddles will meet the needs of a variety of applications.

Features	Benefits	
Thermal key within threshold	Saves energy year round	
Height is a maximum ½ inch	Meets ADA Guidelines for Accessibility	
6063-T6 aircraft aluminum	Durable & long lasting	

## **Applications:**

- Healthcare Facilities
- Schools
- Public Buildings
- Retail
- Food Service

Copyright © 2012-2019, ASSA ABLOY Accessories and Door Controls Group, Inc.










# **Energy Saving and Accessible Solutions**

Pemko has many products that save energy, from adhesive gasketing and astragals to door bottoms and thresholds. Pemko can also help meet barrier free needs with modular ramps, floor treads and commercial thresholds.

### **Available Products**

Part number	Width	Finishes
273x224_FG_	55/16"	Mill Finish Aluminum, Dark Bronze Anodized, Gold Anodized
274x224_FG_	65/16"	Mill Finish Aluminum, Dark Bronze Anodized, Gold Anodized
278x224_FG_	4"	Mill Finish Aluminum, Dark Bronze Anodized, Gold Anodized
279x224_FG_	411/32"	Mill Finish Aluminum, Dark Bronze Anodized, Gold Anodized





For more information about GREENGUARD and GREENGUARD Gold certification, visit www.ul.com/gg.





ASSA ABLOY is a member of the USGBC and CaGBC. U.S. Green Building Council logo is a trademark owned by theU.S. Green Building Council and is used with permission.

Alternate Inserts		
273x224_FGP		
274x224_FGP		
278x224_FGP	pile (P)	
279x224_FGP	F (- )	
273x224_FGV		
274x224_FGV		
278x224_FGV		
	FCO-V/IM (W)	

279x224\_FGV

# **Technical Specifications:**

Threshold Material: 6063-T6 Aircraft Aluminum

Finishes: Mill Finish Aluminum, Dark Bronze

Anodized, Gold Anodized

Thermal Break Material: Black rigid polypropylene

Gasket Material: ThermoSeal™ (FGT), Eco-V™ (FGV), or pile (FGP).

#### **Fasteners:**

Wood Screws included. Other fastener options are available upon request at an additional charge.

#### **Sound Rated:**

Tested to meet ASTM E 90-2009 Standard. Tested to meet ANSI Standard \$12.60-2010, Acoustical Performance Criteria.

#### Fire Rated

Meets UL10C Standard as a Category J gasket.

#### **Smoke Rated:**

Meets requirements of UBC 7-2 and UL 1784 Standards and is tested in accordance with NFPA 105 test method.

#### Air Tested

Air infiltration tested in accordance with ASTM E283-04.

#### **ADA Compliance:**

Meets the barrier free requirements of ICC/ANSI A117.1-2009.

#### ANSI/BHMA:

Meets the requirements of ANSI/BHMA A156.21-2014 Thresholds.

#### **GREENGUARD Gold Certification:**

Meets the product certification requirements for low chemical emissions of UL 2818 to Gold Status.











#### ARCHITECTURAL DOOR ACCESSORIES™

Markar | McKinney | Pemko | Rockwood

ASSA ABLOY Opening Solutions Architectural Door Accessories 5535 Distribution Drive, Memphis, TN 38141 orders.pemko@assaabloy.com www.assaabloydooraccessories.us Memphis, TN USA P: 800 824-3018 F: 800 243-3656 Ventura, CA USA P: 800 283-9988 F: 800 283-4050 Vaughan, ON CA P: 800.461.3007 F: 800.461.8989