

# 1106 SERIES

1106 Series Strikes are fail-secure, weatherproof electric strike for gate locks. One piece strike body made of cast zinc alloy, suitable for cylindrical and mortise locksets and for hollow metal and wood frame doors.


The new water drainage design makes it suitable for use on gates or semi-outdoor applications.

## STANDARD FEATURES

- Fail-secure operation
- Weatherproof
- Static strength 1000 LB (470 KG)
- One piece cast zinc alloy construction
- Non-handed, fully reversible
- Net weight: 343g
- Tested to 250,000+ cycles
- Can be powered by VDC for continuous duty and VAC for intermittent use, (not exceeding 10 seconds)

## COMPATIBLE LOCKS

Designed for Cylindrical Locksets



## SPECIFICATION

MODELS	1106-01	1106-02
VOLTAGE	8-16 VAC Only	12/24 VAC/VDC
FINISH	US28 or US4	
HOLDING FORCE	1000 LB (470KG)	
LATCH THROW	9/16" (15mm)	
KEEPER WIDTH	1 5/8" (41mm)	
DIMENSION	3 1/2" (L) x 1 7/16" (W) x 2 5/8" (D)	
OPERATING TEMP.	14°F to 133°F (-10°C~+45°C)	

## FRAME APPLICATIONS

Hollow Metal

Wood

