

1400 SOLENOID



STANDARD FEATURES

- Rated for continuous for VDC and intermittent duty (not exceeding 10 seconds) for VAC
- Specify **RH** solenoids for Models 1401, 1430LH, 1440LH
- Specify **LH** solenoids for Models 1430RH, 1440RH,
- **1400-G Series** are centerd (non-handed), compatible for all models except 1430 and 1440

SPECIFICATION

MODELS	VOLTAGE	CURRENT DRAW	OHMS
1400-01G	8-16 VAC	0.33~0.8A / 0.75A	16
1400-01R	3-6 VDC*	Ohm's Law	5
1400-01L		Ohm's Law	5
1400-05G	12 VAC/VDC	0.28A	41
1400-05R		0.194A/0.24A	49
1400-05L		0.194A/0.24A	49
1400-08G	24 VAC/VDC	0.16A	148
1400-08R		0.123A/0.146A	164
1400-08L		0.123A/0.146A	164

*intermittent use only at 3-6 VDC

3400 SOLENOID

STANDARD FEATURES

- Rated for continuous duty, VDC only.
- Specify **RH** solenoids for Models 3401, 3430LH, 3440LH, 3460B/RH and 3470B/RH
- Specify **LH** solenoids for Models 3430RH, 3440RH, 3460B/LH and 3470B/LH

SPECIFICATION

MODELS	VOLTAGE	CURRENT DRAW	OHMS
3400-06R	12 VDC	0.24A	50.3
3400-06L			
3400-09R	24 VDC	0.10A	232.2
3400-09L			

1700 SOLENOID



STANDARD FEATURES

- Rated for continuous for VDC and intermittent duty (not exceeding 10 seconds) for VAC
- Adjustable keeper included

SPECIFICATION

MODELS	VOLTAGE	CURRENT DRAW	OHMS
1700-01	8-16 VAC, 3-6 VDC*	0.33~0.8A	16
1700-05	12 VAC/VDC	0.28A	41
1700-07	24 VAC/VDC	0.16A	148
1700-08	24 VDC	0.14A	170

*intermittent use only at 3-6 VDC

ELECTROMAGNETS

ELECTRIC STRIKES

EXIT DEVICES

MISC. ACCESS CONTROL