

1703

STANDARD FEATURES

- Fail-secure, faceplate size 1 1/4" x 6 7/8"
- Anodized aluminum faceplate, suitable for hollow metal, aluminum or wood frames
- Adjustable keeper, depth - 1/2" max latch projection possible with 1/8" door/frame clearance - 3/4"
- Reversible - non-handed
- Limited warranty - 36 months

SPECIFICATION

TAMPER STRENGTH	1000 LB (454 KG)
VOLTAGE	1703-01 8-16 VAC/3-6 VDC 1703-05 12 VAC/VDC 1703-07 24 VAC/VDC 1703-08 24 VDC
FINISH	US28 or US10B



ELECTROMAGNETS

ELECTRIC STRIKES

1704

STANDARD FEATURES

- Fail-secure, faceplate size 1 7/16" x 7 15/16"
- Anodized aluminum faceplate, suitable for hollow metal, aluminum or wood frames
- Adjustable keeper, depth - 1/2" max latch projection possible with 1/8" door/frame clearance - 3/4"
- Reversible - non-handed
- Limited warranty - 36 months

SPECIFICATION

TAMPER STRENGTH	1000 LB (454KG)
VOLTAGE	1704-01 8-16 VAC/3-6 VDC 1704-05 12 VAC/VDC 1704-07 24 VAC/VDC 1704-08 24 VDC
FINISH	US28, US4 or US10B



EXIT DEVICES

MISC. ACCESS CONTROL