


2960

STANDARD FEATURES

- Field reversible: fail-safe or fail-secure
- Dual voltage 12/24 VDC field selectable
- Stainless steel faceplate
- Suitable for narrow frames
- Changeable nib to suit single or double swing doors
- Can be installed in horizontal or vertical position
- Tested to 1,000,000 cycles

SPECIFICATION


VOLTAGE	12/24 VDC
CURRENT DRAW	280 mA/12 VDC, 140 mA/24 VDC
LOCK MONITORING	SPDT rated 3 A/125 VAC
DIMENSION	8 1/4" x 1" x 1 3/4" 5 15/16" x 1 3/16" x 1/16"
OPERATING TEMP.	14°F to 113°F (-10°C~+45°C)



OUTSWING



INSWING



DOUBLESWING



3810

STANDARD FEATURES

- Field reversible: fail-safe or fail-secure
- Dual voltage 12/24 VDC field selectable
- Door/drawer position monitoring, with built-in reed switch bolt monitoring

SPECIFICATION

VOLTAGE	12/24 VDC
CURRENT DRAW	300 mA/12 VDC, 150 mA/24 VDC
DIMENSION	3 3/16" (H) x 1 1/8" (W) x 1 1/8" (D)
HOLDING FORCE	500 LB