



ELECTROMAGNETS

8608 SERIES

STANDARD FEATURES

- Slide-in mounting plate design for easy and secure installation
- Dual voltage 12/24 VDC field selectable
- Built-in MOV spike and surge protection
- No residual magnetism
- Aluminum alloy casing
- Bond sensor output for remote monitoring
- UL Listed for auxiliary locks under file GWXT.R16728




8608-BD




8608-2


APPLICATIONS



OUTSWING



INSWING



DOUBLE DOOR

SPECIFICATION

MODELS	HOLDING FORCE	OPTIONAL FEATURES	CURRENT DRAW	DIMENSIONS
8608	800 LB	BD	500 mA/12 VDC 250 mA/24 VDC	Magnet: 10 7/16" x 1 1/8" x 2 1/16" Armature Plate: 7 1/4" x 9/16" x 1 3/4"
8608-2	800 LB x2	B, BD	500 mA/12 VDC 250 mA/24 VDC	Magnet: 20 7/8" x 1 1/8" x 2 1/16" Armature Plate: 7 1/4" x 9/16" x 1 3/4" x2

NOTES:

B: Bond Sensor; BD: Bond Sensor & Door Status

OPTIONAL BRACKETS

Optional brackets & accessories compatible with 8608 Series Electromagnets

MODELS	DESCRIPTION
21038N	Z-Brackets (For 8608-BD)