

## Rockwood Hinge Side Door Edge Order Form

The global leader in  
door opening solutions

Fill out this form and email to: [orders.rockwood@assaabloy.com](mailto:orders.rockwood@assaabloy.com) / or fax to: 800-922-9212

### Customer Information

Company Name: \_\_\_\_\_ Date: \_\_\_\_\_  
 Account #: \_\_\_\_\_ Phone/Fax: \_\_\_\_\_ / \_\_\_\_\_  
 Email: \_\_\_\_\_ PO #: \_\_\_\_\_

Select a  Mortised  300  301  302  302B  
**Door Edge:**  Non-Mortised  304  305  306-RKW  306-AST  306B  306B-AST  
 308  309  310  310B  310BS  
 Other \_\_\_\_\_

Order Line #: \_\_\_\_\_ Quantity: \_\_\_\_\_ Handing: \_\_\_\_\_ Tag. No's: \_\_\_\_\_

Finish: \_\_\_\_\_

Select Hinge Size,  
Door Type and Fill  
in Dimensions:

UL Rated

\*Door Edge Height if  
different from net  
door height \_\_\_\_\_

### Specify Mounting

(if not standard)

- Torx Screws
- Tek Screws

\* Standard Door Thickness  
is 1 3/4" if not please advise: \_\_\_\_\_

\* Standard Leg Length for non mortised  
edge is 1 1/4" if not please advise: \_\_\_\_\_

\* Standard Leg Length for mortised edge  
is 7/8" if not please advise: \_\_\_\_\_

Note: Your door thickness is a nominal dimension. Doors can vary + or - 1/16" from the nominal dimension. When ordering, verify actual door thickness to assure a working fit of the door edge.

