## Rockwood Products Maintenance Instructions

## **ASSA ABLOY**

The global leader in door opening solutions

For Installation Assistance, Call Our Customer Service At 800-458-2424 • www.rockwoodmfg.com

## **General Maintenance Instructions**

- 1. Periodically check the fasteners and tighten if necessary. The fasteners should not loosen regularly; if they do, there is an installation problem that should be resolved.
- 2. Clean the product routinely by following the cleaning instructions below.

## **Finish Cleaning Instructions**

**CAUTION**: Always try the recommended procedure in a small inconspicuous spot prior to treating the entire article to verify it works on your particular application and you are satisfied with the results.

NOTE: Frequent cleaning extends the life of all finishes.

Finish Code	Finish	Cleaning Instructions
US3	Polished & clear coated brass	Use a soft cloth and mild soap and water. Never use brass polish or an abrasive cleaner unless you intend to remove all clear coat and totally refinish the product.
US3NL	Polished (not clear coated) brass	Use a soft cloth and a good metal cleaner. We recommend Mr. Metal by S. C. Johnson Company.
US4	Satin finish & clear coated brass	Use a soft cloth and mild soap and water. Never use brass polish or an abrasive cleaner unless you intend to remove all clear coat and totally refinish the product.
US9	Polished & clear coated bronze	Use a soft cloth and mild soap and water. Never use brass polish or an abrasive cleaner unless you intend to remove all clear coat and totally refinish the product.
US10	Satin finished & clear coated bronze	Use a soft cloth and mild soap and water. Never use brass polish or an abrasive cleaner unless you intend to remove all clear coat and totally refinish the product.
US10B	Oxidized & oiled bronze	Use a soft cloth and a paste furniture wax. Buff lightly so as not to remove the dark oxide coating where it remains.
US26	Polished chrome plated	Use a soft cloth and a good metal cleaner. We recommend Mr. Metal by S. C. Johnson Company.
US26D	Satin chrome plated	Use a soft cloth and a good metal cleaner. We recommend Mr. Metal by S. C. Johnson Company.
US28	Anodized aluminum	Use a soft cloth and mild soap and water.
313/315	Dark bronze or black anodized aluminum	Use a soft cloth and mild soap and water.
US32	Polished stainless steel	Use a soft cloth and a good metal cleaner. We recommend Mr. Metal by S. C. Johnson Company.
US32D	Satin stainless steel	Use a soft cloth and a good metal cleaner. We recommend Mr. Metal by S. C. Johnson Company.
US32DMS	Satin MicroShield Coated	Use a soft cloth and mild soap and water. Never use brass polish or an abrasive cleaner unless you intend to remove all clear coat and totally refinish the product.
US32D316	Satin stainless steel	Use a soft cloth and a good metal cleaner. We recommend Mr. Metal by S. C. Johnson Company.
US32316	Polished stainless steel	Use a soft cloth and a good metal cleaner. We recommend Mr. Metal by S. C. Johnson Company.
PWT	Polished white tombasil	Use NEVRDULL brand metal cleaner and follow instructions on the product.
	Santoprene™ Grip Zones	Use mild soap and water.
SWT	Satin white tombasil	Use NEVRDULL brand metal cleaner and follow instructions on the product.