

The Exit Check® All-In-One Device integrates our premium Spectra™ bar with SDCs innovative delayed egress electronics. When unauthorized egress is initiated by depressing the push pad of the S6000-101, an audible alarm will sound and an irreversible delay period of 15 seconds will begin. After the delay period has expired, the device unlocks, permitting egress until the device is reset. In a life safety emergency, the device will immediately unlock upon loss of power or when powered by a fire control supervised power supply. **Door contact included for anti tailgate and door prop.**

APPLICATION INCLUDE:

- Restricting the egress of wandering patients for their own safety
- Restricting the egress of commercial center patrons for security application needs
- Controlling pedestrian traffic in transportation facilities, including airport jetways and tarmacs
- Reducing shoplifting and employee theft
- Compatible with access control for entry using electrified trim on rim and vertical rod devices or using mortise case electrification (Not compatible with rim electric strike)

SECURITY


FWAX
SPECIAL LOCKING
ARRANGEMENTS

LISTED

Single: 24VDC @ 540 mA

Pair: 24VDC @ 790 mA

**SDC PUSH UNTIL ALARM
SOUNDS. DOOR CAN BE
OPENED IN 15 SECONDS.**




SPECIFY DEVICE				LIST
S61	Rim mount exit device			665.00
S62	Surface Vertical - ROD GUARDS SUGGESTED			998.00
S63	Mortise <i>[03 Lever Trim included]</i> - specify: EE or GE <i>Eclipse Escutcheon or Galaxy Escutcheon</i>			1,220.00
SPECIFY FUNCTION				
01	Exit Only	02	Dummy	03 Nightlatch N/C
SPECIFY PANIC OR FIRE RATED				Add to List
P	Panic	N/C	F Fire	122.00
SPECIFY HAND (Mortise Only)				
RR	Right hand reverse bevel, RHRB	LR	Left hand reverse bevel, LHRB	N/C
SPECIFY FINISH				
U	630 Dull Stainless Steel			N/C
SPECIFY LENGTH				Add to List
36	For 36" Door (standard) N/C	42	For 42" Door 23.00	48 For 48" Door 45.00


Exit Check® - Delayed Egress All-In-One Device

Distributor Discount Code **XK**

S61000-101 Rim Device
Single Door Application



S62000-101 Surface
Vertical Rod Device
Double Door Application



SPECIFY DELAYED EGRESS

Add to List

101	Electrification of master exit device and integrated controller with key switch control and reset, less cylinder	1,497.00
DES	For pair of doors, additional exit device equipped with delayed egress mechanism, less integrated controller. Must be ordered together with 101 device.	555.00

SPECIFY OPERATION

If no Code is specified - ND is the SDC STANDARD OPERATIONS MODE for this product

NC	IBC, IFC, NFPA 101, NFPA 1-UFC, UBC, SBC Compliant Fixed 15 exit delay, 1 or 2 second nuisance delay Calif. Building Code OSHPD/Manual Power Up	N/C
ND	IBC, IFC, NFPA 101, NFPA 1-UFC, UBC, SBC Compliant Fixed 15 exit delay, 1 or 2 second nuisance delay	N/C
BC	BOCA National Building Code and Chicago Building Code 15 second fixed exit delay, 0 second nuisance delay, auto reset 30 seconds after door closure	N/C
BD	BOCA National Building Code 15 second fixed exit delay, 1 or 2 second nuisance delay, auto reset 30 seconds after door closure	N/C

SPECIFY TRIM (optional)

Add to List

FOR S61 RIM AND S62 SURFACE ONLY - FOR S63 TRIM SEE PAGE 47

Mechanical Trim (less cylinder)

EK03U	Eclipse Escutcheon	GK03U	Galaxy Escutcheon	249.00
--------------	--------------------	--------------	-------------------	---------------

Electric Trim (FOR RIM AND VERTICAL ROD ONLY)

Failsecure, field reversible to failsafe; 4 ft cable and connectors; 600/300 mA @ 12/24VDC

EKE03U	Eclipse style electric trim less mortise cylinder, Stainless Steel Finish	748.00
GKE03U	Galaxy style electric trim less mortise cylinder, Stainless Steel Finish	748.00

Electronically Controlled Trim (FOR MORTISE ONLY)

MS	Failsafe	MF	Failsecure	222.00
-----------	----------	-----------	------------	---------------

TRIM OPTIONS Rim Cylinder Required for 03 function, Mortise Cylinder Required for S6300 Add to List

CYL-6KDQ	6 pin, 1.125" mortise cylinder, keyed different, dull chrome	49.00
CYL-6KAQ	6 pin, 1.125" mortise cylinder, keyed alike, dull chrome	49.00
RIM-CYL-KA	Rim Cylinder for 03 Function, keyed alike - see page 45 for more info	37.00

SPECIFY POWER TRANSFER (For the entire line of Power Transfer, see page 97 and page 98)

LIST

PTM-10AL	(10) Cond., 5 Amp @ 12/24V AC/ DV, Alum US28	383.00	PTH-10Q	(10) Cond., 1 Amp @ 12/24V per pair, 4.5" x 4.5"	217.00
PT-5	UL Listed Concealed Power Transfer Device, less wires	67.00	PT-3V	Armored flex conduit, less wires, with wire junction box	50.00

SPECIFY POWER SUPPLY (For the entire line of Power Supplies, see page 100)

LIST

602RF	1 Amp, class 2 output, 12" W x 12" H x 3.75" D box	284.00
631RF	1.5 Amp, class 2 output, 12" W x 12" H x 3.75" D box	381.00

Note: 600 series Power Supply required with S6000-101 for UL listing



EK



GK



EKE



GKE



PTM Series



PTH x 5
Ft Cable



PT5



PT-3V

602RF
(shown)



600 Series
Power Supply