SP-CR701 CUSTOM DOUBLE LIPPED STRIKE AND RESCUE STOP FOR 1-3/4" DOOR, 1/8" INSET, CYLINDRICAL LATCH, 6-7/8" FRAME — 7 1/2 — STOP IS SPRING LOADED **ABH DOOR STOP COVER DIMENSIONS** MAY NOT MATCH OTHER MANUFACTURERS MAKING PART NON-HANDED — 6 7/8 FRAME – **BUT INSTALLATION IS** STILL HANDED DOOR STOP-+ 1 → **COVER** 45° 45° 1 5/8 7/16-7/16 -€ OF DOOR C OF FRAME R1/8 TYP. 2 3/4 2 1/8 5/16 2 3/8 2 3/8 **€** OF DOOR REINFORCEMENT: WHEN INSTALLING IN METAL FRAME, REINFORCEMENT IS **NEEDED** WITH THIS PRODUCT, CUSTOMER OR MANUFACTURER TO SUPPY FRAME REINFORCEMENT WITH LATCH BOLT CLEARANCE 2-5/16 MIN. CLÉARANCE FOR DOOR STOP COVER CENTERED (2) REINFORCEMENT PLATES SUPPLIED BY DOOR FRAME **MANUFACTURER** 1-1/2 MIN. CLEARANCE FOR DOOR STRIKE CENTERED ORDER #:_____ 1. HORIZONTAL CENTERLINE OF PLATE TO MATCH HORIZONTAL CENTERLINE OF CUTOUT. ORDER DATE:_____ **CUT-OUT FOR** 2. SCREWS 8-32 X 3/8" UNDERCUT F.H.M.S. 3. R.H. DOOR SHOWN, L.H. OPPOSITE **METAL JAMB** CUSTOMER: Architectural Builders Hardware Mfg., Inc. CUSTOMER PO#:_____ 1222 Ardmore Ave., Itasca, IL 60143 MATERIAL:_____ 630.875.9900; FAX 800.9FAXABH (932.9224) www.abhmfg.com

Email: abhinfo@abhmfg.com

QUANTITY:_