SP-CR710 CUSTOM DOUBLE LIPPED STRIKE AND RESCUE STOP FOR 1-3/4" DOOR, 1/8" INSET, CYLINDRICAL LATCH, 8" FRAME STOP IS SPRING LOADED **-85/8**-MAKING PART NON-HANDED — 8 FRAME -**BUT INSTALLATION IS** STILL HANDED DOOR STOP -**COVER** 45° 45° 1 5/8 7/16 -7/16 **ABH DOOR STOP COVER DIMENSIONS** MAY NOT MATCH OTHER MANUFACTURERS € OF DOOR - 11/16 C OF FRAME R1/8 TYP. 2 3/4 2 1/8 1 1/4 **€** OF DOOR 5/16 -2 7/8 2 7/8 REINFORCEMENT: WHEN INSTALLING IN METAL FRAME, REINFORCEMENT IS **NEEDED** WITH THIS PRODUCT, CUSTOMER OR MANUFACTURER TO SUPPY FRAME REINFORCEMENT WITH LATCH BOLT CLEARANCE 2-5/16 MIN. CLÉARANCE FOR DOOR STOP COVER CENTERED (2) REINFORCEMENT PLATES SUPPLIED BY DOOR FRAME **MANUFACTURER** 1-1/2 MIN. CLEARANCE FOR DOOR STRIKE CENTERED ORDER #:_____ 1. HORIZONTAL CENTERLINE OF PLATE TO MATCH HORIZONTAL CENTERLINE OF CUTOUT. ORDER DATE:_____ **CUT-OUT FOR** 2. SCREWS 8-32 X 3/8" UNDERCUT F.H.M.S. 3. R.H. DOOR SHOWN, L.H. OPPOSITE **METAL JAMB** CUSTOMER: Architectural Builders Hardware Mfg., Inc. CUSTOMER PO#:_____ 1222 Ardmore Ave., Itasca, IL 60143 MATERIAL:_____ 630.875.9900; FAX 800.9FAXABH (932.9224) www.abhmfg.com QUANTITY:_ Email: abhinfo@abhmfg.com