SP-CR744 CUSTOM DOUBLE LIPPED STRIKE AND RESCUE STOP FOR 1-3/4" DOOR, 1/8" INSET, MORTISE LOCK, NO DEADBOLT, 4-1/2" FRAME **ABH DOOR STOP COVER DIMENSIONS** -51/8-STOP IS SPRING LOADED **MAY NOT MATCH OTHER MANUFACTURERS** MAKING PART NON-HANDED 4 1/2 FRAME-DOOR STOP **BUT INSTALLATION IS COVER** STILL HANDED 45° 45° 1 5/8 7/16-7/16 -¢ OF DOOR 13/16 **€** OF FRAME - 13/32 R1/8 TYP. 2 3/4 2 1/8 1 1/2 **€** OF DOOR 5/16 REINFORCEMENT: WHEN INSTALLING IN METAL FRAME, REINFORCEMENT IS **NEEDED** WITH THIS PRODUCT, CUSTOMER OR MANUFACTURER TO SUPPY FRAME REINFORCEMENT WITH LATCH BOLT CLEARANCE 2-5/16 MIN. CLÉARANCE FOR DOOR STOP COVER CENTERED (2) REINFORCEMENT PLATES SUPPLIED BY DOOR FRAME MANUFACTURER 1-1/2 MIN. CLEARANCE FOR DOOR STRIKE CENTERED NOTE: ORDER #:_____ 1. HORIZONTAL CENTERLINE OF PLATE TO MATCH HORIZONTAL CENTERLINE OF CUTOUT. ORDER DATE:_____ **CUT-OUT FOR** 2. SCREWS 8-32 X 3/8" UNDERCUT F.H.M.S. 3. R.H. DOOR SHOWN, L.H. OPPOSITE **METAL JAMB** CUSTOMER: **Architectural Builders Hardware Mfg., Inc.** CUSTOMER PO#:_____

MATERIAL:_

QUANTITY:_

1222 Ardmore Ave., Itasca, IL 60143 630.875.9900; FAX 800.9FAXABH (932.9224) www.abhmfg.com

www.abhmfg.com Email: abhinfo@abhmfg.com