



Hole Chart

Hole	Size		Used For:
	H.M. Door	Wood Door	
A	1-1/8 (29) Dia.	1-1/8 (29) Dia.	Lever/Knob
B	1-1/4 (32) Dia.	1-1/4 (32) Dia.	Cylinder
C	3/4 (19) Dia.	3/4 (19) Dia.	Thumbturn or Emergency Key
D	3/4 (19) Dia.	3/4 (19) Dia.	Hotel Indicator
H	.116 (2.9) Dia. #32 Drill	1/16 (1.6) Dia.	Surface Escutcheon Plate Attaching Screws

Notes:

1. All dimensions given in inches (mm).
2. Do Not Scale.

**All Series Mortise Locks
Wood and H.M. Door Preparation
Surface Applied Escutcheon Plate Trim**



1-800-438-1951
www.yalelocks.com

TEMPLATE NUMBER	SHEET	DATE
7086-1301	1 of 2	05-13

Lock Function					Holes in Door	
4600	8600	8700	8800		Outside	Inside
4601	8601	8701 8770DT 8771DT 8772DT	8801 8870DT 8871DT 8872DT		A, H	A, H
4680	8680	8780	8880			
4681	8681	8781	8881			
4684	8684	8784 836A & B 838A & B	8884 836A & B 838A & B			
4602	8602	8702	8802	8865	A, C, H	A, C, H
4605	8605	8705	8805			
4607	8607	8707	8807		A, B, H	A, H
4608	8608	8708	8808			
4624	8624		8824 8831			
4690	8690	8790	8890		A, B*, H	A, B*, H
4691	8691	8791	8891			
4660-2	8660-2	8717-2 8730-2 8760-2	8808-2 8811-2 8812-2	8830-2 8860-2 8894-2	A, B, H	A, B, H
4694-2	8694-2	8794-2	8817-2	8895-2		
4695-2	8695-2	8795-2	8818-2			
4620	8620	8720 8727	8820 8827		A, B, D, H	A, C, H
4622	8622	8722	8822	8861		
4632	8632	8732	8832	8867		
	8647	8747	8840	8809	A, B, H	A, C, H
4660	8660	8760	8847			
4667	8667	8767	8860			
		8728	8828		None	A, H
	8633		8833		B, H	A, H
	8634 8634-2		8834 8834-2		B, H	A, B, H
			8813-2 8814-2	8833-2	B, H	B, H
			8813 8815		B, H	C, H
			8814		B, H	None
			8823	8829	A, B, H	None
			8835		None	A, C, H

* Lock can be mounted with cylinder outside or inside. Check for proper application.

**All Series Mortise Locks
Wood and H.M. Door Preparation
Surface Applied Escutcheon Plate Trim**



1-800-438-1951
www.yalelocks.com

TEMPLATE NUMBER	SHEET	DATE
7086-1301	2 of 2	05-13