

V96 – Von Duprin 996L



The easier and more affordable solution

The Command Access electronic modification of the **Von Duprin 996L series exit trim** is perfect for stairwell conditions or applications where electric pullback of the exit device's latchbolt is cost prohibitive or not required. This is especially practical in applications where fire/life safety codes require "fail safe" condition which is not an option with electrified latch pullback devices. Because the current draw is quite low there is no need for a more expansive power supply to provide the surge current. These trims are purchased complete or as modifications only.

U.S. Customer Support
1-888-622-2377

Visit our website for more details
www.CommandAccess.com

Canada Customer Support
1-855-823-3002



Models Available

V96EL - storeroom:
(fail safe)

Outside lever locked (EL) electronically. Applied power prohibits outside lever from retracting latch(es). Outside key momentarily unlocks outside lever to retract latch(es). Inside push pad is always free for immediate egress.

V96EU - storeroom:
(fail secure)

Outside lever unlocked (EU) electronically. Applied power allows outside lever to retract latch(es). Outside key momentarily unlocks outside lever to retract latch(es). Inside push pad is always free for immediate egress.

Lever Styles Available

06, 17

Please call for availability of additional lever

Finishes Available

626

Please call for availability of additional finishes

FEATURES:

- Continuous duty solenoids used to insure trouble-free operation
- Internally mounted solenoid to ease installation (no special door prep required)
- No hassle 3-Year Warranty

OPTIONS:

- Available Fail Safe (Electrically Locked) or Fail Secure (Electrically Unlocked)
- Voltage options - 12V or 24V (AC/DC)
- REE - Request to Enter switch available
- CRU2 - Current Reduction Unit to improve solenoid life in "continuously on" applications

SPECIFICATIONS:

- Operating Voltage - 12 or 24VAC/DC (+or- 10%) (must specify 12 or 24 volts when ordering)
- Amperage - 12V = 250 mA / 24V = 150 mA
- Solenoid coil resistance - 12V = 49 Ω / 24V = 159 Ω

Model No.	Notes:		
Customer:	Job No./Name:	Date:	Provided by: