

LINE X-X CORRESPONDS TO
LINE X-X ON DEVICE TEMPLATE

X

LHR SHOWN
RHR OPPOSITE

☉ CORRESPONDS TO CENTER
LINE OF DEVICE ON
DEVICE TEMPLATE

1" CLEAR DEPTH REQUIRED

INSIDE
FACE OF
LOCK STILE

X

1/2" DIA
2 HOLES

1/8" R
4 PLACES

9/16"

3 1/8"

23/32"

1 7/16"

X

OUTSIDE
FACE OF
LOCK STILE

DEVICE APPLICATION SCHEDULE

| |
|--------------------------------|
| 33A/35A RIM DEVICE |
| 33/3527A VERTICAL ROD DEVICE |
| 33/3527A-F VERTICAL ROD DEVICE |
| 33/3547A VERTICAL ROD DEVICE |
| 33/3547A-F VERTICAL ROD DEVICE |
| 33/3548A VERTICAL ROD DEVICE |
| 33/3548A-F VERTICAL ROD DEVICE |
| 33/3549A VERTICAL ROD DEVICE |
| 33/3549A-F VERTICAL ROD DEVICE |

FOR CUTOUT ON
INSIDE FACE OF
DOOR SEE DEVICE
TEMPLATE

388NL CYLINDER CONTROL

VON DUPRIN®

NOTES: SEE MASTER SHEET #10001 FOR SUGGESTED REINFORCING

TEMPLATE
NUMBER:

40079_d

DATE:
05-31-13