

# ELECTRA PRO™ SDC Z7200 Series Heavy Duty Cylindrical Locksets

Distributor Discount Code **LEK**

**Function: 7200 Series Locksets** are locked on the outside and unlocked from the exterior by an access control or mechanical key. The inside lever is always operable for uninhibited egress.

**Latch Status Output:** Standard with all SDC brand Z7200 locksets. SPDT, 3 Amps @ 30VDC

## FEATURES

- Choice of failsecure or failsafe mode
- Dual 12/24 VDC
- **Latch Status Output:** Z7200 standard
- 'C' type keyway, BEST IC core optional
- Independent lever power return springs
- Power Regulator Module included for Z7250 Model only

## SPECIFICATIONS

<b>Dual Voltage</b>	600/300 mA @ 12/24VDC	<b>Backset</b>	2.75
<b>Certification</b>	Exceeds ANSI A156-2-4000 Grade 1	<b>Strike</b>	4.875 strike ANSI A115.2
<b>Latchbolt</b>	0.5625"	<b>Door Thickness</b>	1-5/8" to 2-1/8"



Electrically Controlled Single Point Locks & Latches, 3 Hr A Label Fire Doors



Electra Pro™ Z7250G

SPECIFY MODEL				LIST
<b>Electra Pro™ Locks</b>				
<b>Z7250</b>	SDC Failsafe, with Latch Status Output	<b>Z7252</b>	SDC Failsecure, with Latch Status Output	<b>457.00</b>



Electra Pro™ Z7250E

SPECIFY LEVER TRIM				
<b>SDC Lever Trim</b>				
<b>G</b>	Galaxy	<b>E</b>	Eclipse	<b>N/C</b>
<b>G5</b>	<b>Galaxy, I-Core prep</b>	<b>E5</b>	<b>Eclipse, I-Core prep</b>	<b>28.00</b>
<i>G5 and E5 I-Core prep without I-Core</i>				



G Galaxy

SPECIFY FINISH					Add to List
<b>Q</b>	626 Dull Chrome (standard)	<b>N/C</b>			
<b>C</b>	605 Bright Brass	<b>56.00</b>	<b>H</b>	613 Oil Rubbed Bronze	<b>56.00</b>
<b>D</b>	606 Dull Brass	<b>56.00</b>	<b>P</b>	625 Bright Chrome	<b>56.00</b>



E Eclipse

OPTIONS				Add to List
<b>R</b>	Request-to-exit output, operates on activation of inside lever, SPDT 0.1A @ 30VDC			<b>128.00</b>
<b>NOTE:</b> REX Output Replaces Latch Status Output				



G5 Galaxy, I-Core prep

OPTIONAL CYLINDER and I-CORES				Add to List
<b>SDC Conventional Cylinders (Schlage 'C' Keyway Standard)</b>				

<b>6PKA</b>	6 PIN Keyed alike	<b>N/C</b>	<b>6PKD</b>	6 PIN Keyed different (standard)	<b>N/C</b>
-------------	-------------------	------------	-------------	----------------------------------	------------

### [IC] Interchangeable Core (Best 'A' Keyway Standard) - requires E5 or G5 lever trim

<b>IC7P-KA</b>	7 pin I-Core, small format, keyed alike	<b>56.00</b>	<b>IC7P-KD</b>	7 pin I-Core, small format, keyed different	<b>56.00</b>
----------------	---	--------------	----------------	---	--------------



E5 Eclipse, I-Core prep



I-CORE

OPTIONAL LATCH AND BACKSET ASSEMBLIES					
<b>B1</b>	2-3/4" Backset latchbolt (Standard)	<b>N/C</b>	<b>B2</b>	2-3/8" Backset latchbolt (Optional)	<b>26.00</b>

OPTIONAL STRIKE PLATES					
<b>ST1</b>	ANSI 1-1/4" x 4-7/8" (Standard)	<b>N/C</b>	<b>ST2</b>	T-Strike with dust box, 1-1/8" x 2-3/4" MUST BE SPECIFIED	<b>N/C</b>