



Full Height Turnstile

FHT1000 Full Height Turnstile **FHT1011** Full Height Turnstile (RFID Access Control System)

FHT1022 Full Height Turnstile (Fingerprint and RFID Access Control System)

The ZKAccess FHT1000 Full Height Turnstile is a rugged cost-effective entrance control system designed for high-traffic volume.

FHT1000 is a full height turnstile series designed to provide the utmost perimeter security. The possibility of tailgating and "hop-overs" is completely eliminated.

Besides securing door entrances and interior lobbies, the perimeter security of a building is an important extra layer of protection from unauthorized visitors. FHT1000 is an all metal full height turnstile that is extremely durable & secure and is suitable for outside use. Its rugged construction ensures trouble free and dependable operation.

FHT1000 metal barriers are normally held in a locked position, thus denying passage to the secured side. Upon FHT1000's reader (RFID and/or fingerprint) positively recognizing a user's valid access card or fingerprint, its barriers unlock automatically, thus allowing users passage to the secured side.

During emergencies and power outages the barriers automatically unlock, thereby ensuring users FAST unencumbered exit to safety.

FHT1000 provides both **security** and **convenience**, all in a very durable yet clean design.

Built-in Reader Integration









- FHT1000 series ships already integrated with our customers' preference for either card or fingerprint access control reader. This greatly reduces installation time & expense.
- FHT1000 series and associated access control readers are all factory-tested prior to shipping.
- ZKAccess provides true plug 'n play turnstiles with the lowest possible total cost of ownership in the industry!


Specifications

Power Supply		AC110V/220V, 50/60Hz
Power consumption	Starting	20W
	Standby	7W
	Unlock	22W
Working temperature		-28°F to 140°F
Working humidity		0% ~ 95%
Working environment		Indoor/Outdoor
Speed of throughput	RFID	Maximum 30/minute
	Fingerprint	Maximum 25/minute
	Face	Maximum 15/minute
	Vein	Maximum 15/minute
Lane width		24 inches (60 mm)
Footprint		63 x 54 inches (1600 x 1380 mm)
Dimension		63(l) x 54(w) x 93(h) inches (1600(l) x 1380(w) x 2350(h) mm)
Dimension with packing		48(I) x 96(w) x 34(h) inches (1230(I) x 2450(w) x 860(h) mm)
Net weight		606 lbs (275kg)
Weight with packing		794 lbs (360 kg)
LED indicator		Υ
Cabinet material		SUS304 Stainless Steel
Barrier material		SUS304 Stainless Steel
Barrier movement		Rotating
Emergency mode		Υ
Security level		High
MCBF		2 million cycles

Dimensions







ZKTeco USA

6 Kingsbridge Road, Unit 8, Fairfield, NJ 07004 Phone: (862) 505-2101 • Fax: (862) 204-5906 • sales@zkaccess.com • www.zkaccess.com

