



FR1200-ID
IP65-rated Outdoor
Slave Fingerprint Reader

IP65 rated Fingerprint Slave Reader for ZK inBio panels and standalone reader controllers



Small Form Factor:

Sealed Enclosure with slim and attractive design are ideal for indoor and outdoor mounting.



Communication:

FR1200-ID can be connected to RS485 port of any ZKAccess inBio Panel or F18-ID fingerprint reader.



Waterproof Enclosure:

FR1200-ID is an IP65 rated wateroof reader that can be used for many outdoor applications. The cables and connectors are epoxy sealed at the back of the reader.



Easy Operation:


Once user places their finger on FR1200-ID its fingerprint is matched by either ZK's standalone reader controller (master reader) or ZK's inBio Panel. It also provides Visual indication for acceptance/rejection of the fingeprint of the users.




Options:

FR1200-ID is an IP65 rated wateroof reader that can be used for many outdoor applications.

Installation with inBio Panel



Master/Slave Standalone Installation



Specification

Communication

RS485

Power

12V DC, 1A

Optional Function

Mifare Card

Waterproof Enclosure

IP65 Rated

Dimensions

Length: 3in (7.62cm) Width: 1.6in (4cm) Depth: 1.1in (2.8cm) Weight: 0.27lbs (0.12kg)

Environment

Operating Temperature: 32° to 113° F (0° to 45° C)

Operating Humidity: 20% to 80%

Part Numbers

FR1200-ID with ZKACcess ID card reader FR1200-M with Mifare card reader

What's in the Box




FR1200-ID



Installation Template



Back Plate



Rubber Gasket



Network Cable



Screws



ID Card



Metal Mounting Plate

ZKTeco USA

6 Kingsbridge Road, Unit 8, Fairfield, NJ 07004

Phone: (862) 505-2101 • Fax: (862) 204-5906 • sales@zkaccess.com • www.zkaccess.com

