



KR702E

ZKAccess Proximity card reader

KR702E is an IP65-rated weather resistant single-gang ZKAccess proximity card reader.

Due to its convenient single-gang size, KR702E is the ideal card access solution for any metal doors with thin frames, parking gates, fences, turnstiles or any security device having a narrow mounting surface.

KR702E also comes with a keypad which provides users both added security and convenience.

KR702E has a built-in Wiegand-Out port which can be connected to most any access control panel (including ZKAccess C3 and InBio door controllers).

Specifications

Technology	Proximity
Supported card types	ZKAccess 125 KHz (optional Mifare)
Mounting	Single-gang
Indoor & Outdoor Installation	Electronics sealed in weather and tamper-resistant epoxy potting
Keypad	12 keys (0-9, *, #)
Wiegand Interface	Wiegand-Out port
Power Supply	12V DC
IP-rating	65
Operating Temperature	-32 F to 158 F (0 °C- 70 °C)
Operating Humidity	20% - 80%
Dimensions (HxWxD)	4.4 x 3 x .6 inches (113 x 75 x 16 mm)
Certifications	CE, FCC
Current draw	30 mA typical, 75 mA peak @ 12V DC
Read range	Up to 3 inches (80 mm)

ZKTeco USA

6 Kingsbridge Road, Unit 8, Fairfield, NJ 07004
Phone: (862) 505-2101 • Fax: (862) 204-5906 • sales@zkaccess.com • www.zkaccess.com