



SBT3000 Series

SBT3000 Single Lane Swing Barrier Turnstile **SBT3011** Single Lane Swing Barrier Turnstile (w/ controller and RFID reader)

SBT3022 Single Lane Swing Barrier Turnstile (w/ controller and combination fingerprint & RFID reader)

The ZKAccess SBT3000 single lane swing barrier turnstile is a compact and elegant cost-effective entrance control system designed for high-traffic volume.

The SBT3000 is a single lane swing barrier turnstile series designed for smooth and silent operation and draws very little power. It's made of stainless steel which makes SBT3000 highly durable. SBT3000 is also surprisingly compact and designed to operate in small work places.

SBT3000 tempered-glass barriers are normally held in a locked position, thus denying access to the secured side. Upon SBT3000's reader (RFID and/or fingerprint) positively recognizing a user's valid access card or fingerprint, its barriers automatically swing open, thus allowing users passage to the secured side.

Option for built-in REX button allows users to conveniently exit the secured side without needing to use their access card or fingerprint.

During emergencies and power outages the barriers automatically swing open, thereby ensuring users FAST unencumbered exit to safety.

SBT3000 provides both **security** and **convenience**, all in a very durable yet elegant compact design.

Built-in Reader Integration








- SBT3000 series ships already integrated with our customers' preference for either card or fingerprint access control reader. This greatly reduces installation time & expense.
- SBT3000 series and associated access control readers are all factory-tested prior to shipping.
- ZKAccess provides true plug 'n play turnstiles with the lowest possible total cost of ownership in the industry!

Specifications

•	
Power Supply	AC 220V/110V, 50/60Hz
Operating Temperature	-18F to 140F degrees
Operating Humidity	5%-85%
Working Environment	Indoor/Outdoor (if sheltered)
Rated Power	60W
Traffic Throughput	30 passages per minute
Casework Material and Barrier Material	SUS304 stainless steel and tempered glass
Visual Indicator	Yes. Access granted/denied and walking direction (entry or exit)
Audio Alarm	Yes
Control System	Input controlled by dry contact
Emergency Button Input	Yes
Infrared sensor	Triggers alarm upon detection of unauthorized users and tailgaters
Turnstile Dimension	39.3 (h) x 18.38 (w) x 63.2 (d) inches
Wooden Crate Dimension	59 x 43 x 33 inches
Turnstile Weight	315.26 lbs.
Turnstile and Wooden Crate Combined Weight	467.4 lbs.

Dimensions (inches)



ZKTeco USA

6 Kingsbridge Road, Unit 8, Fairfield, NJ 07004 Phone: (862) 505-2101 • Fax: (862) 204-5906 • sales@zkaccess.com • www.zkaccess.com

