



Multi-Credential Options



PHONE



SMART WATCH



SMART REMOTE



13.56 MHz



PIN



KEY



EXTERIOR VIEW



INTERIOR VIEW

Product Features

Access Types

Smartphone, PIN access codes, RFID, smart remote, smartwatch, traditional key override. Two-factor authentication capable

Access Levels

Administrator defined through the Cloud Based Access Control Interface

Max Users

1000 users locally, Unlimited in the cloud

Audit Trail

Real time events tracking through the app or Cloud Based Access Control Interface. Event filtering and report exporting is standard.

Notifications

Email or SMS notifications, Administrator defined through the Cloud Based Access Control Interface

Programmed

All user and credential data is added through the Cloud Based Access Control Interface

Communication

Hybrid BLE and ANT+ wireless mesh network

Security

Patented End2End AES 128-bit with Cypher Block Chaining

Power Source

4 AA alkaline batteries

Back set

ADJ 2-3/8", 2-3/4"

Door Thickness

1-3/8" - 1-3/4" conventional cylinder, 1-3/4" SFIC

Thumbturn

ADA compliant

Handing

Non-handed, field reversible

Operation

Always locked or can be set to Passage mode.

Chassis

Built on PDQ KM heavy-duty chassis

Cylinders

Conventional, SFIC, High Security and UL 437

Keying

22 keyways plus Restricted, High Security and UL 437

Keypad

Capacitive touch, back lit. Integrated Mifare RFID reader

Certifications

UL 20 min other ratings pending.

Environment

Suitable for interior/exterior applications -31 to 150F weatherized

Retrofits

Easy retrofits, utilizes standard 161 door prep

Remote Operation

Remotely operated and controlled via our wireless mesh network

Upgradeable

Over the Air Firmware ensures the products remain cyber secure and evolve capabilities over time

Typical Applications

- Multi-Family
- Assisted Living
- Hospitality
- Government Facilities
- Offices / Co-Working Spaces
- Public Buildings
- Retail
- Medical/ Dental Clinics
- K-12 / Higher Ed / Private Schools
- Industrial
- Warehouses / Distribution Facilities
- Manufacturing Companies
- Maintenance areas
- Houses of Worship
- Airports and Transit Centers

Architectural Finishes



605 (US3)
Bright Brass

613 (US10B)
Oil Rubbed Bronze

622 (US19)
Flat Black

626 (US26D)
Satin Chromium

Cylinders



Wireless Networked Smart Locking Solutions



Grade 1
Cylindrical
GTS-XLS



Heavy-Duty
Deadbolt
KMS-XLS




Grade 2
Cylindrical
SDS-XLS



Grade 1
Mortise
MRS-XLS



Heavy-Duty
Exit Device Trim
6EWS-XLS



Standard-Duty
Interconnected
CLS-XLS*



*Contact factory for availability

Headquarters: 2230 Embassy Drive, Lancaster, PA 17603
 Phone: 866.874.3662 | Email: smartsupport@pdqlocks.com
www.pdqsmartnetworked.com